Awesomatix A800MMX MMCX

Setup: My Base Setup · Hobby Bobby · Sep 21, 2021

so dialed
Open/save in RC Setup App →

Scan to open in the app

FRONT SUSPENSION

Anti-roll bar	1.1mm 1 strip
Bellcrank position	Rearward
Camber	-1.5 degrees
Caster	4 degrees
Differential height	Low
Downstop	6.0 mm
Lower arms	Standard 1+9.0 (#C04M1+9.0)
LOWER ARMS	
Inner pivot spacers - front	3.0 mm
Inner pivot spacers - rear	3.0 mm
Outer stud spacers	0 mm
Ride height	5.2 mm
Steering arms	Kit
Steering blocks	Kit
Steering crank type	Kit
STEERING LINK	
Inner stud spacers	1.0 mm
Outer stud location	Front
Outer stud spacers	4.0 mm
Steering rack spacers	0 mm
Toe	+1 degrees
Upper arm mounts	Kit
UPPER ARMS	
Inner stud location - front	1 - Inside
Inner stud location - rear	1 - Inside
Inner stud spacers - front	4.5 mm
Inner stud spacers - rear	4.5 mm
Outer stud spacers	1.75 mm
Wheel hex	Standard

REAR SUSPENSION

Anti-roll bar	1.1mm 1 strip
Camber	-2 degrees
Caster	2 short degrees
Differential height	High
Downstop	5.4 mm
Lower arms	Standard 1+8.0 (#C04M1+8.0)
LOWER ARMS	
Inner pivot spacers - front	3.0 mm
Inner pivot spacers - rear	3.0 mm
Outer stud spacers	3.0 mm
Ride height	5.4 mm
Steering arm	Kit
Steering blocks	Kit
Toe	-2.5 degrees
TOE LINK	
Inner stud spacers	0 mm
Outer stud spacers	3.75 mm
Upper arm mounts	Kit
UPPER ARMS	
Inner stud location - front	A - Inside
Inner stud location - rear	A - Inside
Inner stud spacers - front	4.0 mm
Inner stud spacers - rear	4.0 mm
Outer stud spacers	1.75 mm
Wheel hex	Standard

TIRES

	FRONT	REAR
Tire additive	Sxt	–
Tire brand / type	Gravity	–
Tire glue diameter	57mm	–

SHOCKS

	FRONT	REAR
A distance	3 mm	3 mm
B distance	3 mm	2 mm
Damper	Kit (#D2.2-S-P)	Kit (#D2.2-S-P)
Oil weight	550 cst	550 cst
PSS	0 %	0 %
Rotor	Kit	Kit
Springs	Soft	Soft
SRS/RHS arrangement	I	I
Shock oil brand	Team Associated	

DIFFERENTIALS

	FRONT	REAR
Diff pulley	38T	38T
Diff type	Spool	Gear
Diff fluid	–	10,000 cst
Diff fluid brand	AE	

DRIVETRAIN

Belt anti-skip system	None
Belts	Kit
Drive ratio - final	2.85
Drive ratio - internal	1.9
Driveshafts - front	US-Spec
Driveshafts - rear	Standard

BODY & CHASSIS

Chassis	C01B-X-MMA Aluminum
Top stiffener - front	
Top stiffener - rear	None
Upper deck - front	MMX
Upper deck - rear	MMX
Upper deck screws	C, D, F
Weight balance (F/R)	50 / 50
Weight: total	1355 g