AE RC10 B6.2 D

Setup: RC-TORREFARRERA Xmas Race Setup · Joan Ribalta (E1RC) · May 3, 2021

so dialed
Open/save in RC Setup App →

Scan to open in the app

TRACK

Track	RC-TORREFARRERA
Type	Outdoor clay
Grip / moisture	Medium / Muddy
Surface / layout	Smooth / Medium
Air temp	8°C (46°F)
Track temp	4°C (39°F)

FRONT SUSPENSION

Anti-roll bar	None
Arms	Flat
Axle height	0 mm
Bulkhead	Aluminum Factory Team
Camber	-1 degrees
CAMBER LINK	
Inner stud location	2 - Middle
Inner stud spacers	1.0 mm
Outer stud location	A - Inside
Caster	27.5 deg - Kick-up: 25 / Block insert: +2.5
Ride height	22 mm
SHOCKS	
Arm mounting hole	B - Middle
Tower mounting hole	3 - Outside
STEERING LINK	
Inner stud spacers	1.0 mm
Outer stud spacers	0 mm
Steering plate / arm	+1mm
Steering stop spacers	0 mm
Toe	+1 degrees
Tower	Flat
Trail	4 mm
Wheel hex	5mm Aluminum
Wheelbase (hub carrier spacers)	Short (back)

NOTES 1mm spacer entre chasis y bulkhead

ELECTRONICS

Battery brand	Gens Ace
Battery C rating	60/120
Battery capacity	4600 mAh
Battery model	Shorty
ESC brand	Hobbywing
ESC model	Xr10pro 160
Motor brand	Hobbywing
Motor Kv constant	5120 Kv
Motor model	Xerun g3 7.5t
Motor timing	30 degrees
Motor wind	7.5 turns
Radio brand	Sanwa/Airtronics
Radio model	M12s
Receiver brand	Sanwa/Airtronics
Receiver model	482
Servo brand	Savox
Servo model	1258

REAR SUSPENSION

Anti-roll bar	None
Arms	73 mm
Axle height (hub insert)	0 (0/3 up)
C mount	Brass 23g
C mount inserts	0 - center
Camber	-1 degrees
CAMBER LINK	
Inner stud location	2 - Middle
Inner stud spacers	3.0 mm
Outer stud mount spacers	2.0 mm
Outer stud spacers	2.0 mm
D mount	Brass
D mount inserts	1 down and out
Differential height	0 mm
Hubs	Plastic
Ride height	22 mm
Shock location	Front of arm
SHOCKS	
Arm mounting hole	C - Outside
Tower mounting hole	2 - Middle
Wheel hex	7mm
Wheelbase (arm spacers)	Short (forward)
Wheelbase (hub spacers)	Short (forward)

BODY & CHASSIS

	FRONT	REAR
Wing	Kit	Schumacher

Battery position	Rear hole / 5
Body	Kit
Chassis	Kit
Rear wing angle	6 degrees
Weight balance (F/R)	40 / 60
WEIGHT	
Electronics plate	13g Aluminum
Servo	None

SHOCKS

	FRONT	REAR
Bodies	Kit	Kit
Cup offset	5 mm	5 mm
Eyelet length	Short	Long
Limiters (external)	0 mm	1 mm
Limiters (internal)	1	0
Oil weight	32.5 wt	27.5 wt
Pistons	2 x 1.6mm FT v2	2 x 1.7mm FT v2
Shafts	v2 3x21mm TiN	v2 3x27.5mm TiN
Springs	v2 Green - lightest	v2 White
Stroke	23 mm	28 mm
Shock oil brand	Team Associated	

DRIVETRAIN

Clutch pads	Schelle triad
Clutch type	Slipper
Differential type	Ball
Driveshaft CVA pin location	Towards wheel
Driveshafts	67mm
Pinion	23 teeth
Spur	78 teeth
Transmission gears	3
Transmission orientation	Layback

TIRES

	FRONT	REAR
Tire brand / type	Jconcepts Ribs	Proline Blockade
Tire compound	Green	M4
Tire insert	Open-cell	Open-cell
Wheel brand / type	Schumacher	Schumacher