Tekno EB410.2

Setup: My Base Setup · Edward Richards (Papas trailer) · Feb 16, 2022

so dialed
Open/save in RC Setup App →

Scan to open in the app

FRONT SUSPENSION

A mount inserts	0 - center
Anti-roll bar	1.5 mm
B mount inserts	1 down
Camber	-2 degrees
CAMBER LINK	
Inner stud location	2 - Middle
Outer stud location	A - Inside
Outer stud spacers	0
Caster	15 degrees
Droop	78 mm
Kick-up angle	11 degrees
Ride height	21 mm
SHOCKS	
Arm mounting hole	B - Outside
Tower mounting hole	2 - Middle-in
Steering blocks	Kit
STEERING LINK	
Inner stud spacers	4
Outer stud spacers	2
Steering stop spacers	0 mm
Sweep	0 degrees
Toe	+0.5 degrees
Wheel hex	+1mm Composite mm
Wheelbase (arm spacers)	Front 2.0mm / rear 0.0mm (short)

REAR SUSPENSION

Anti-roll bar	1.7 mm
Arms	Kit
Axle height (hub insert)	Dot up (high)
C mount inserts	0.5 down
Camber	-2 degrees
CAMBER LINK	
Hub insert / stud location	D down - Outside bottom
Inner stud location	Middle
D mount inserts	1 out
Droop	89 mm
Ride height	20 mm
SHOCKS	
Arm mounting hole	A - Inside
Tower mounting hole	2 - Middle-in
Toe	-2 degrees
Wheel hex	Lightened steel
Wheelbase (arm spacers)	Front 1.0mm / rear 1.0mm
Wheelbase (hub spacers)	Front 1.0mm / rear 1.0mm

BODY & CHASSIS

	FRONT	REAR
Wing	–	Kit
Body	Kit	
Center diff brace	Kit	
Rear brace	Long	
Rear wing height	5 mm	
Rear wing position	7 - rear (wing forward)	

SHOCKS

	FRONT	REAR
Caps	Aluminum Emulsion	Kit
Limiters (internal)	0	0
Oil weight	600 cst	600 cst
Pistons	8 x 1.2mm	8 x 1.3mm
Rebound	0 %	0 %
Shafts	Kit	Kit
Shock type	Emulsion	Emulsion
Springs	Red - stiffest	Pink - lightest
Stroke	23 mm	29 mm
Shock oil brand	Tekno	

DIFFERENTIALS

	FRONT	REAR
Diff fluid	15,000 cst	10,000 cst
Center diff fluid	30,000 cst	

DRIVETRAIN

Spur	81 teeth

ELECTRONICS

Battery C rating	100
ESC brand	Maclan
Motor brand	Maclan
Motor timing	45 degrees
Motor wind	13.5 turns
Radio brand	Hitec
Radio EPA steering	70 %
Radio EPA throttle	75 %
Servo brand	ProTek