AE RC10 T6.1

Setup: Indoor clay · Greg Cipres · Jan 31, 2022

so dialed
Open/save in RC Setup App →

Scan to open in the app

TRACK	
Track	Rainman's
Type	Indoor clay
Grip / moisture	High / Wet
Surface / layout	Medium / Medium

RESULTS	
Best lap	16.431 s

FRONT SUSPENSION

Anti-roll bar	White 1.2mm
Arms	Kit
Axle height	1 mm
Bulkhead	Plastic
Camber	-1 degrees
CAMBER LINK	
Inner stud location	2 - Middle
Inner stud spacers	1 mm
Outer stud location	B - Outside
Caster	30 deg - Kick-up: 25 / Block insert: +5
Ride height	29 mm
SHOCKS	
Arm mounting hole	B - Middle
Tower mounting hole	2 - Middle
STEERING LINK	
Inner stud spacers	2 mm
Outer stud spacers	1 mm
Steering plate / arm	Kit
Steering stop spacers	0 mm
Toe	0 degrees
Tower	Kit
Track: wheel hexes	8.5 mm
Trail	4 mm
Wheelbase: hub carrier spacers	Long (forward)

TIRES

	FRONT	REAR
Tire brand / type	Raw speed	Raw speed
Tire compound	Soft/yellow	Soft/yellow

NOTES Apply sticky kicks purple/gold tire sauce 2 minutes before race

REAR SUSPENSION

Anti-roll bar	None
Arms	Kit
Axle height: hub insert	0 (0/3 up)
C mount	Aluminum
C mount inserts	0.5 down and out
Camber	-1 degrees
CAMBER LINK	
Inner stud location	2 - Middle
Inner stud spacers	1 mm
Outer stud location / hub insert	3 holes up / C - Middle up
Outer stud spacers	0
D mount	Aluminum
D mount inserts	1 up
Differential height	0 mm
Hub	Plastic
Ride height	27 mm
Shock location	Back of arm
SHOCKS	
Arm mounting hole	C - Middle-out
Tower mounting hole	2 - Middle
Tower	Kit
Track: wheel hexes	7mm
Wheelbase: hub spacers	Middle

BODY & CHASSIS

Battery position	Front hole / 2
Body	Pro-Line Enforcer
WEIGHT	
Chassis	0g
Electronics plate	0 g
Servo	0 g

SHOCKS

	FRONT	REAR
Bodies	v2 12x27.5mm	v2 12x36mm
Cup offset	5 mm	5 mm
Eyelet length	Long	Long
Limiters (inner/outer)	2 / 0 mm	1 / 0 mm
Oil weight	30 wt	30 wt
Pistons	2 x 1.6mm FT v2	2 x 1.7mm FT v2
Shafts	3x27.5mm v2 Ti-N	3x35mm v2 Ti-N
Springs	54mm White	72mm Green - lightest
Stroke	26.5 mm	35 mm
Shock oil brand	Team Associated	

DRIVETRAIN

Clutch pads	Kit
Clutch type	Slipper
Differential type	Ball
Driveshafts	91mm
Pinion	26 teeth
Spur	78 teeth
Transmission gears	3
Transmission orientation	Layback

ELECTRONICS

Battery brand	ProTek
Battery capacity	6100 mAh
ESC brand	Hobbywing
Motor brand	Trinity
Motor timing	45 degrees
Servo brand	Savox