Yokomo YZ-2 CAL3

Setup: Dcmcc · Green (Yokomo) · Aug 26, 2021

so dialed
Open/save in RC Setup App →

Scan to open in the app

EVENT	
Event	Club

TRACK	
Track	Dcmcc
Type	Outdoor astroturf
Grip / moisture	Medium / Dry
Surface / layout	Medium / Medium
Air temp	20°C (68°F)
Track temp	22.5°C (73°F)

FRONT SUSPENSION

Arms	Kit
Axle height (hub spacers)	Top 1.0mm / bottom 1.5mm
Camber	-2.0 degrees
Camber block	Aluminum Wide
CAMBER LINK	
Inner stud location	2 - Middle
Inner stud spacers	1 mm
Outer stud location	A - Inside
Caster (hub carrier inserts)	+5 degrees (5 up)
Hub carrier	Hard
Ride height	16 mm
SHOCKS	
Arm mounting hole	C - Outside
Tower mounting hole	1 - Inside
Steering block	Hard
Steering block orientation	A'/B'
Steering center link	Aluminum
Steering center link spacers	2.0 mm
STEERING LINK	
Inner stud spacers	2 mm
Outer stud spacers	1 mm
Steering plate / arm	Graphite 1mm offset
Suspension mount	Steel
Toe	0 degrees
Tower	Gull type graphite -3mm
Wheel hex	4.3mm Aluminum
Wheelbase (hub carrier spacers)	Long (hub forward)

REAR SUSPENSION

Anti-roll bar	0.9 mm
Arms	Kit
Axle height (hub insert)	+0.5mm (1 down)
Camber	-2.0 degrees
Camber block	Plastic
Camber block orientation	Protrusion upward
CAMBER LINK	
Inner stud location	2 - Outside
Inner stud spacers	3 mm
Outer link mount spacers	0 mm
Outer stud location	2 holes front / A - Inside
Outer stud spacers	1 mm
Differential height	+1mm (1 up)
Hub	Kit
RF mount	Standard
RF mount inserts	0.5 down
Ride height	16 mm
RR mount	Standard
RR mount inserts	1 down
Shock location	Front of arm
SHOCKS	
Arm mounting hole	B - Mid-in
Tower mounting hole	2 - Middle
Tower	Graphite -3mm
Wheel hex	5mm Kit
Wheelbase (arm spacers)	Short (hub forward)
Wheelbase (hub spacers)	Short (hub forward)

TIRES

	FRONT	REAR
Tire brand / type	Schumacher	Schumacher
Tire compound	Yellow	Mezzo yellow
Wheel brand / type	Jc slim	Yokomo
Tire insert	–	Schunacher medium

SHOCKS

	FRONT	REAR
Bodies	Kit	Kit
Eyelet length	Medium	Long
Limiters (external)	0 mm	0 mm
Limiters (internal)	0.5 mm	0.5 mm
Oil weight	450 cst	350 cst
Pistons	2 x 1.6mm, 2.0mm thick black	2 x 1.8mm, 2.0mm thick black
Springs	RPU Purple - stiffest RPU	Carpet RPU Black - lightest RPUC
Stroke	22 mm	28 mm
Shock oil brand	Yokomo	

DRIVETRAIN

Differential fluid	5,000 cst
Differential type	Ball
Driveshafts	Universal
Spur	80 teeth
Transmission case	Laydown carpet

BODY & CHASSIS

	FRONT	REAR
Wing	Kit	LMR27
Battery position	Front post / 3	
Body	Kit	
Chassis	CA L3	
Front bulkhead mount	Plastic	
Rear wing angle	High degrees	
Weight - battery	None	
Weight - chassis	None	
Weight: electronics plate	Steel 36g	