AE RC10 B6.1

Setup: Foam · Kristian Lennartsson · Sep 20, 2020

so dialed
Open/save in RC Setup App →

Scan to open in the app

TRACK

Type	Indoor carpet
Grip / moisture	High
Surface / layout	Smooth / Medium

FRONT SUSPENSION

Anti-roll bar	None
Arms	Rpm gullwing
Axle height	3 mm
Bulkhead	Revolution design brass
Camber	0 degrees
CAMBER LINK	
Inner stud location	2 - Middle
Inner stud spacers	1 mm
Outer stud location	A - Inside
Caster	30 deg - Kick-up: 25 / Block insert: +5
Ride height	15 mm
SHOCKS	
Arm mounting hole	B - Middle
Tower mounting hole	2 - Middle
STEERING LINK	
Inner stud spacers	0 mm
Outer stud spacers	0 mm
Steering plate / arm	+1mm
Steering stop spacers	0 mm
Toe	+1 degrees
Tower	Gull-wing
Trail	4 mm
Wheel hex	5 mm
Wheelbase (hub carrier spacers)	Long (forward)

REAR SUSPENSION

Anti-roll bar	Gray (1.3mm)
Axle height (hub insert)	+3 mm (0/3 down)
C mount	Aluminum
C mount inserts	1 out
Camber	-1.5 degrees
CAMBER LINK	
Hub insert / stud location	3 holes down / C - Middle down
Inner stud location	1 - Inside
Inner stud spacers	3 mm
D mount	Aluminum
D mount inserts	1 in
Differential height	3 mm
Hub	Aluminum FT
Ride height	16 mm
Shock location	Front of arm
SHOCKS	
Arm mounting hole	C - Middle-out
Tower mounting hole	2 - Middle
Wheel hex	6mm
Wheelbase (hub spacers)	Long (back)

BODY & CHASSIS

	FRONT	REAR
Wing	None	Kit
Battery position		Front hole / 5
Body		Kit
Rear wing angle		6 degrees
WEIGHT		
Electronics plate		Steel g
Servo		Steel g

SHOCKS

	FRONT	REAR
Bodies	Team FOX	Team FOX
Cup offset	5 mm	0 mm
Eyelet length	Short	Long
Limiters (internal)	0	0
Oil weight	40 wt	30 wt
Pistons	2 x 1.6mm FT v2	2 x 1.8mm FT v2
Shafts	v2 3x21mm TiN	v2 3x27.5mm TiN
Springs	v2 Red	v2 Blue
Stroke	21 mm	28 mm
Shock oil brand	Team Associated	

DRIVETRAIN

Clutch pads	Kit
Clutch type	Slipper
Differential fluid	30,000 cst
Differential type	Gear
Driveshafts	67mm
Pinion	23 teeth
Spur	78 teeth
Transmission gears	3
Transmission orientation	Laydown

ELECTRONICS

ESC brand	Skyrc ts160
Motor model	6.5t
Motor timing	30 degrees
Motor wind	6.5 turns
Servo brand	Srt
Servo model	6012