Xpress EXECUTE XQ10

Setup: Halifax - Wet - Modified · Mark Raddenbury (Speedrc.co.uk) · Feb 13, 2023

so dialed
Open/save in RC Setup App →

Scan to open in the app

EVENT

Event	BRCA Nationals

TRACK

Track	Halifax
Type	Outdoor asphalt
Grip / moisture	Low / Wet
Surface / layout	Smooth / Medium

FRONT SUSPENSION

Arms	Hard
Camber	-2 degrees
CAMBER LINK	
Inner mount spacers	0
Inner stud mount	Inside
Inner stud spacers	1.5 mm
Outer stud spacers	0.5 mm
Downstop	5 mm
FF mount	Aluminum
FF mount inserts	0 center
FR mount inserts	0 center
FR mounts	Split aluminum
Hub carriers	Hard
Ride height	5.4 mm
Servo saver stud spacers	3.0 mm
SHOCKS	
Arm mount spacers	0 mm
Tower mount spacers	0 mm
Tower mounting hole	3mm
Steering blocks	Hard
STEERING LINK	
Inner stud spacers	1.0 mm
Outer stud location	1 - Outside
Outer stud spacers	1.0 mm
Steering plate spacers	1.0 mm
Toe	-1 degrees
Tower	Kit
Track: wheel hexes	Red
Wheelbase: arm spacers - F/R	1 / 1 mm

NOTES Xsquare low CoG mounts

REAR SUSPENSION

Arms	Hard
CAMBER LINK	
Inner mount spacers	0 mm
Inner stud mount	Outside
Inner stud spacers	1.5 mm
Outer stud location	A - Inside
Outer stud spacers	2.0 mm
Downstop	4.2 mm
Hubs	Hard
OPCS link stud spacers - inner/outer	- / - mm
RF mount	Aluminum
RF mount inserts	0 center
Ride height	6 mm
RR mount inserts	0 center
RR mounts	Split aluminum
SHOCKS	
Arm mount spacers	0 mm
Tower mount spacers	0 mm
Tower mounting hole	2.5mm
Tower	Kit
Track: wheel hexes	Red
Wheelbase: arm spacers - F/R	1 / 1 mm

NOTES Xsquare low CoG mount

TIRES

	FRONT	REAR
Tire brand / type	Shimuzu	Shimuzu
Tire compound	Wet	Wet

ELECTRONICS

Battery brand	Nosram
Battery capacity	6400 mAh
ESC brand	Hobbywing
Motor brand	Hobbywing
Motor model	G3 5t
Motor timing	20 degrees
Motor wind	5 turns
Radio brand	Futaba
Receiver brand	Futaba
Steering servo brand	Turnigy
Steering servo model	D99x

NOTES Minimal punch, no boost, 20° turbo

SHOCKS

	FRONT	REAR
Oil weight	450 cst	450 cst
Pistons	4-hole	4-hole
Springs	2.6-2.8	Silver medium
Stroke	9.0 mm	9.0 mm
Shock oil brand	RcRacePrep	

DIFFERENTIALS

	FRONT	REAR
Diff fluid	–	5,000 cst
Diff fluid mass	–	1.3 g

DRIVETRAIN

Drive ratio - final	7.25
Drive ratio - internal	1.9
Driveshafts - front	Universal Double Joint
Driveshafts - rear	Universal
Front drive type	Spool
Pinion	22 teeth
Spur	84 teeth

BODY & CHASSIS

Body	Zooracing Wolverine
Body position	5mm forward
Center post	No
Chassis	2.25mm Graphite
Motor mount screws	2 F
Rear wing	Bittydesign Hard Mod
Under-chassis stiffener - front	None
Under-chassis stiffener - rear	None
Upper deck stiffener	Composite
Weight: total	1324 g
Weights	Front: 0g / Front left: 10g / Front right: 10g / Battery: 0g / Rear left: 0g / Rear right: 11g