TLR 22 5.0 DC Elite

Setup: My Base carpet set up. · Adam Kingscott · Apr 21, 2024

so dialed
Open/save in RC Setup App →

Scan to open in the app

TRACK

Track	Rotherham RC club
Type	Indoor carpet
Grip / moisture	Medium / Dry
Surface / layout	Smooth / Medium

FRONT SUSPENSION

Anti-roll bar	None
Arm length (VLA setting)	Short arm
Arms	Stiffezel
Axle height	0mm top / 4mm below (low)
Camber	-1.5 degrees
CAMBER LINK	
Inner stud location	3 - Outside
Inner stud spacers	0 mm
Outer stud location	A - Inside
Outer stud spacers	2 mm
Hub carrier	5 degrees
Kick shims	3 mm (low roll center)
Kickup	25 degrees
Pivot	Composite
Ride height	15 mm
SHOCKS	
Arm mounting hole	B - Middle
Tower mounting hole	1 - Inside
STEERING LINK	
Inner stud location	Standard
Inner stud spacers	0 mm
Outer stud location	Standard
Outer stud spacers	1 mm
Steering plate / arm	5
Toe	0 degrees
Tower	Carbon +2mm
Track: axle spacing	0 mm
Trail	4 mm

ELECTRONICS

Battery brand	IP
Battery capacity	4400 mAh
Battery model	Platinum series
ESC brand	Hobbywing
ESC model	XeRun XR10 PRO 2GS
ESC settings	Hobbywing 2wd mod
Motor brand	Dash
Motor model	R Tune V3
Motor wind	8.5 turns
Radio brand	Futaba
Radio model	T4GRS
Receiver brand	Futaba
Receiver model	R304SB E
Servo brand	Savox
Servo model	0256B

REAR SUSPENSION

Anti-roll bar	None
Arms	VHA Stiffezel
Axle height	4 mm
C mount	Aluminum
C mount inserts	1 down and out
Camber	-1 degrees
Camber block spacer	+1 mm
CAMBER LINK	
Inner stud location	2 - Front (laydown)
Inner stud spacers	1 mm
Outer stud location	B - Front
Outer stud mount spacers	0 mm
Outer stud spacers	0 mm
D mount	Aluminum
D mount inserts	0 center
Differential height	0 mm
Driveshaft CV pin position	2
Hub	Gen II
Ride height	15 mm
Shock location	Front of arm
SHOCKS	
Arm mounting hole	B - Middle
Tower mounting hole	2 - Middle
Tower	Carbon Laydown +2mm
Track: wheel hexes	Kit
Wheelbase: hub spacers	Front 1.5mm / rear 1.5mm

TIRES

	FRONT	REAR
Tire brand / type	Schumacher cut stagger slim	Schumacher cactus yellow.
Tire compound	Yellow	Yellow
Tire insert	Closed-cell	Closed-cell
Tire prep	None	None
Wheel brand / type	JC	TLR

ESC SETTINGS

Boost: Activation	Rpm

SHOCKS

	FRONT	REAR
Bodies	G3 36.5mm x 3.5mm	G3 42mm x 3.5mm
Eyelet length	Standard	Standard
Limiters (external)	0 mm	1 mm
Limiters (internal)	0 mm	0 mm
Oil weight	32.5 wt	37.5 wt
Pistons	G3 2 x 1.6mm	G3 1.6mm / 1.7mm
Shafts	3.5mm x 42.7mm	3.5mm x 48.7mm
Spring cups	Medium	Low
Springs	Orange	LF Yellow
Stroke	22 mm	28.5 mm

Shock oil brand	Team Losi

DRIVETRAIN

Clutch pads	Kit
Clutch type	Slipper
Differential type	4-gear
Driveshafts	67mm CVA
Pinion	22 teeth
Spur	78 teeth
Transmission orientation	Laydown

BODY & CHASSIS

	FRONT	REAR
Wing	Low	TLR 6.5"

Battery position	4
Body	Proline Axis
Chassis	Kit
Chassis brace/waterfall	Stiffezel
Chassis front brace	Standard
Rear wing angle	4 degrees
Rear wing height	Standard
Rear wing wickerbill	2 lines
WEIGHT	
Battery plate	0 g
Electronics plate	Carbon
Rear ballast	0 g