Xpress EXECUTE XQ2S 4WD

Setup: V1 · Nuno Gaspar · Aug 19, 2022

so dialed
Open/save in RC Setup App →

Scan to open in the app

TRACK

Type	Outdoor asphalt
Grip / moisture	Medium / Dry
Surface / layout	Medium / Medium/Open
Air temp	27.5°C (82°F)
Track temp	47.5°C (118°F)

RESULTS

Race type	Practice
Best lap	18.65 s

FRONT SUSPENSION

Ackermann: inner link spacers	0 mm
Anti-roll bar	1.4 mm
Arms	Medium
Camber	-2 degrees
CAMBER LINK	
Inner stud location	Front
Inner stud spacers	1.0 mm
Outer stud spacers	0 mm
Differential height	Low
Downstop	5 mm
FF mount	Aluminum
FF mount inserts	0 center
FF mount spacers	0 mm
FR mount	Split aluminum
FR mount inserts	0 center
FR mount spacers	0 mm
Hub carriers	Medium 4-deg
Ride height	5.3 mm
SHOCKS	
Arm mount spacers	1.0 mm
Tower mount spacers	1.0 mm
Tower mounting hole	1 - Inside
Steering block plates	Medium
Steering blocks	Medium
STEERING LINK	
Outer stud location	1 - Outside
Outer stud spacers	1.0 mm
Steering plate spacers	1.0 mm
Toe	-1 degrees
Tower	FRP 3.0mm Short
Track: wheel hexes	Composite
Wheelbase: arm spacers - F/R	- / - mm

REAR SUSPENSION

Anti-roll bar	1.3 mm
Arms	Medium
Camber	-2 degrees
CAMBER LINK	
Inner stud location	Rear
Inner stud spacers	1.0 mm
Outer stud location	A - Inside
Outer stud spacers	1.5 mm
Differential height	Low
Downstop	4.5 mm
OPCS link stud spacers - inner/outer	- / - mm
RF mount	Split Aluminum
RF mount inserts	0 center
RF mount spacers	0 mm
Ride height	5.5 mm
RR mount	Solid aluminum
RR mount inserts	0 center
RR mount spacers	0 mm
SHOCKS	
Arm mount spacers	1.0 mm
Tower mount spacers	1.0 mm
Tower mounting hole	2 - Middle
Toe	+4 mm
Tower	FRP 3.0mm Short
Track: wheel hexes	Composite
Uprights	Medium
Wheelbase: arm spacers - F/R	- / - mm

TIRES

Tire glue diameter - F/R	- / - mm

SHOCKS

	FRONT	REAR
Bodies	Composite short	Composite short
Oil weight	300 cst	300 cst
Pistons	4-hole	4-hole
Springs	TRF S	TRF M
Stroke	10.5 mm	10.5 mm

Shock oil brand	Medialpro

DIFFERENTIALS

	FRONT	REAR
Diff fluid	–	5,000 cst
Diff fluid mass	–	1.1 g

Front diff type	Spool

DRIVETRAIN

Drive ratio - internal	1.9
Driveshafts - front	XQ1-S Universal
Driveshafts - rear	XQ1-S Universal
Front drive type	Spool
Pinion	40 teeth
Spur	96 teeth

BODY & CHASSIS

Bumper	Foam light
Center post	Yes
FLEX	
Chassis	FRP 2.5mm
Motor mount screws	1 - Front, 2, 3, 4, 5
Upper deck	FRP 2.0mm v2
Upper deck collar	Low flex
Upper deck stiffener location	Front (low flex)
Motor location	Rear