TLR 8IGHT-X Elite

Setup: Ryan/Don setup. 26.5.2020 · Burty · Jun 20, 2021

so dialed
Open/save in RC Setup App →

Scan to open in the app

FRONT SUSPENSION

A mount inserts	0 middle
Anti-roll bar	2.6mm
Arm inserts	Carbon
Axle height	Low
B mount inserts	0.5 down
Camber	-1.5 degrees
CAMBER LINK	
Inner stud location	4 - Inside mid-top
Outer stud location	B - Outside
Hub carrier	Aluminum 17.5 deg
Kick-up	12 degrees
Ride height	27 mm
SHOCKS	
Arm mounting hole	B - Outside
Tower mounting hole	3 - Middle-out
STEERING LINK	
Inner stud location	1 - Back
Inner stud spacers	2 mm
Outer stud spacers	1 mm
Toe	+1 degrees
Tower	Aluminum - Black
Wheel hex	Kit

BODY & CHASSIS

Body	Kit
Center diff brace	Carbon fiber
Chassis rib brace	Carbon
Engine mount	Aluminum quick-change
Front brace	Aluminum
Front chassis brace	Kit
Rear wing	TLR Plastic
Rear wing spacer	10 mm
Rear wing wickerbill	0.250

NOTES Rear out drives used in front.
HD rod ends
Titanium turnbuckles

REAR SUSPENSION

Anti-roll bar	2.6mm
Anti-squat / C block inserts	2.0 degrees - 0
Arm inserts	Plastic
Axle height	Middle
Camber	-1 degrees
CAMBER LINK	
Inner stud location	3 - Inside middle
Outer stud location	C - MIddle-out
Hub	Aluminum
Mud guards	Kit
Ride height	27 mm
Shock location	Back of arm
SHOCKS	
Arm mounting hole	B - Outside
Tower mounting hole	3 - Middle
Toe plate / D block insert	-3.0 degrees - 0
Tower	Aluminum - Black
Wheel hex	0mm
Wheelbase (hub spacers)	Front 0mm / rear 3mm (short)

ENGINE

Engine brand	Novarossi
Engine model	Rolling
Fuel	Maxima 30
Glow plug	CT06
Head clearance	Stock
Pipe / header	9886 ss / 41021

TIRES

	FRONT	REAR
Tire brand / type	Proline	–
Wheel brand / type	Losi Stiffezel	Losi

SHOCKS

	FRONT	REAR
Oil weight	47.5 wt	42.5 wt
Pistons	5 x 1.5mm	4x1.5, 1x1.9 taper
Shafts	3.5mm	3.5mm
Shock length	34.52 shaft length mm	43.1 shaft length mm
Shock type	Emulsion	Emulsion
Springs	EVO 4.9 Green	EVO 3.8 Red
Shock oil brand	Team Losi	

NOTES Front 47= 1/3 50 & 2/3 45

DIFFERENTIALS

	FRONT	REAR
Diff fluid	7,000 cst	4,000 cst
Center diff case	Heavy duty	
Center diff fluid	7,000 cst	

NOTES Al pins all diffs

DRIVETRAIN

Clutch shoes & springs	2 blue aluminum shoes with gold springs, 2 composite shoes with green springs
Driveshafts - front	Universal
Driveshafts - rear	Universal
Driveshafts - rear pin location	Toward axle
Pinion	13 teeth
Spur	48 teeth

ELECTRONICS

Radio brand	Sanwa/Airtronics
Radio model	M17
Receiver battery	Muchmore 2500 lipo
Receiver brand	Muchmore
Receiver model	Sana'a rx493
Steering servo brand	Futaba
Steering servo model	S9352HV
Throttle servo brand	Futaba
Throttle servo model	S9352HV
Transponder ID	5857006