Serpent SRX8 PRO

Setup: Trains and lanes · Kyle Loy (Serpent usa) · May 16, 2021

so dialed
Open/save in RC Setup App →

Scan to open in the app

EVENT	
Event	Opener plus cash race

TRACK	
Track	Trains and lanes opener
Type	Outdoor hard-packed
Grip / moisture	High / Dusty
Surface / layout	Rutted / Medium
Air temp	85°F (29°C)
Track temp	82°F (28°C)

RESULTS	
Best lap	0 s
Average lap	0 s

FRONT SUSPENSION

Anti-roll bar	2.3mm
Arm inserts - bottom	Nylon
Arm inserts - top	Nylon
Camber	-3 degrees
CAMBER LINK	
Inner stud location	2 - Inside middle
Outer stud location	B - Middle
Hub carriers	SPT
Kick-up: FF mount inserts	10.5 degrees
Ride height	25 mm
SHOCKS	
Arm mounting hole	A - Inside
Tower mounting hole	2 - Middle-in
Steering arm	Type 2
Steering block	SPT
Steering stop	0.0 mm
Toe	+1 degrees
Tower	Aluminum
Track: wheel hexes	+1mm

NOTES Running light weight hex, and axle

BODY & CHASSIS

Body	Lfr
Chassis	Pro chassis
Engine mount	Kit
Rear wing	Tekno Lightweight
Rear wing angle	2 degrees
Rear wing mount	SRX8 v2
Transmission brace - front	Kit
Transmission brace - rear	Kit

REAR SUSPENSION

Anti-roll bar	2.5mm
Anti-squat: RF block inserts	2.0 degrees - middle
Arm inserts - bottom	Nylon
Arm inserts - top	Nylon
Camber	-3 degrees
CAMBER LINK	
Inner stud location	3 - Inside mid-top
Outer stud location	D - Outside
Hubs	Kit
Ride height	27 mm
SHOCKS	
Arm mounting hole	B - Middle
Tower mounting hole	3 - Middle
Toe: RR block inserts	2.75 degrees
Tower	Aluminum
Track width: hub pin position	Wide (pin in)
Track: wheel hexes	+0mm
Wheelbase: hub spacers	+2.5 mm

NOTES Light weight hex, axle

ENGINE

Engine brand	Os speed
Engine model	Ad2
Fuel	Tessman blend
Glow plug	P3

SHOCKS

	FRONT	REAR
Oil weight	35 wt	30 wt
Pistons	6x1.3	6x1.3 and 1.4
Shafts	TiN Coated	TiN coated
Shock length	108 mm	126 mm
Shock type	Emulsion	Emulsion
Springs	4.9 lb Pink	3.2 lb Red

Shock oil brand: Team Associated

DIFFERENTIALS

	FRONT	REAR
Diff fluid	7,000 cst	3,000 cst
Diff mass	44.75 g	44.75 g
Diff type	HTD	HTD

Center diff case	Standard
Center diff fluid	7,000 cst
Center diff mass	45.7 g
Center diff type	HTD

DRIVETRAIN

Clutch bell	Standard
Clutch shoes & springs	4 carbon shoes / 0.9mm springs
Driveshafts - front	98mm
Driveshafts - rear	98mm
Flywheel	Aluminum
Pinion	13 teeth
Spur	46 teeth