Serpent SRX4 Gen3

Setup: Trains and Lanes 11/14/21 · Ken Grace (Serpent America) · Feb 28, 2023

so dialed
Open/save in RC Setup App →

Scan to open in the app

EVENT	
Event	Season Opener
Class	4x4 Stock Buggy

TRACK	
Track	Trains and Lanes
Type	Indoor carpet
Grip / moisture	High / Dry
Surface / layout	Smooth / Tight

RESULTS	
Race type	Main
Race number	5
Finish	5th

FRONT SUSPENSION

Ackermann: steering plate	1 notch
Anti-roll bar	1.6 mm
Arms	Hard
Axle height spacers - top/bottom	1 / 2 mm
Camber	0 degrees
CAMBER LINK	
Inner stud location	1 - Bottom
Outer stud location	B - Outside
Outer stud spacers	1 mm
Caster: hub carrier inserts	10 degrees
Differential height	High
FF mount inserts	1 out
FR mount inserts	1 in
FR mounts	Brass
Ride height	13 mm
SHOCKS	
Arm mounting hole	Front of arm / A - Inside
Tower mounting hole	2 - Middle
STEERING LINK	
Inner stud spacers	1 mm
Outer stud spacers	1 mm
Steering stop spacers	0 mm
Toe	0 degrees
Tower	Carbon
Track: wheel hexes	SRX4 +0mm

TIRES

	FRONT	REAR
Tire brand / type	Schumacher Cactus Fusion 2	Pro-Line Pyramid
Tire compound	Yellow	Z3
Tire insert	Open-cell	Open-cell
Wheel brand / type	Serpent SDX FR	Serpent
Tire prep	Front sidewall glued	

REAR SUSPENSION

Anti-roll bar	1.5 mm
Arms	SRX2 v2 Hard
Axle height: hub inserts	+3 mm
Camber	-2 degrees
CAMBER LINK	
Inner stud location	2 - Middle
Inner stud spacers	2 mm
Outer mount spacers	2.5 mm
Outer stud location	Outside
Outer stud spacers	0.5 mm
Differential height	High
RF mount inserts	1 out
Ride height	13 mm
Roll center spacer	No
Roll: axle pin position	Middle
RR mount inserts	1 in
SHOCKS	
Arm mounting hole	B - Middle
Tower mounting hole	2 - Middle
Tower	Carbon
TRACK	
Hub inserts	+3 mm
Hubs	Stock
Wheel hexes	SRX2 +1mm
Wheelbase: hub spacers	Long (back)

BODY & CHASSIS

	FRONT	REAR
Wing	–	7.0" v2
Battery position		Stock
Body		Lightweight
Chassis		Kit
Rear wing angle		0 degrees

SHOCKS

	FRONT	REAR
Cup offset	High	Low
Limiters - int/ext	2 / 0 mm	2 / 0 mm
Oil weight	500 cst	500 cst
Pistons	2 x 1.6mm	2 x 1.7mm
Rebound	0 %	0 %
Shafts	Kit	Kit
Shock type	Emulsion	Emulsion
Springs	3.7 lb Green	Astro 2.1 lb Blue
Stroke	20.5 mm	28 mm
Shock oil brand	Serpent	

NOTES Conical pistons down

DIFFERENTIALS

	FRONT	REAR
Diff fluid	15,000 cst	10,000 cst
Diff mass	19.1 g	17.4 g
Diff fluid brand	Serpent	

NOTES Slipper. No center diff for this car

DRIVETRAIN

Clutch setting	1.5-2mm from end of shaft
Drive ratio - final	8.00:1
Drive ratio - internal	2.43:1
Drive type	Slipper
Driveshafts - front	Kit
Driveshafts - rear	Kit
Pinion	24 teeth
Spur	78 teeth

ELECTRONICS

Battery brand	VooDoo Racecells
Battery C rating	120C
Battery capacity	6000 mAh
Battery model	HeadHunter
ESC brand	Maclan
ESC model	M32T Pro160
Motor brand	Trinity
Motor model	X-Factor Certified
Motor timing	51.4 degrees
Motor wind	13.5 turns
Radio brand	Sanwa/Airtronics
Radio model	M17
Receiver brand	Sanwa/Airtronics
Receiver model	RX-492
Servo brand	Sanwa/Airtronics
Servo model	PGS-LH II

NOTES SXR mode for ESC and Servo