AE RC10 B6

Setup: My Base Setup · Rafał Wiszniewski · Mar 1, 2021

so dialed
Open/save in RC Setup App →

Scan to open in the app

FRONT SUSPENSION

Anti-roll bar	None
Arms	Gull-wing
Axle height	2 mm
Bulkhead	Plastic
Camber	-1 degrees
CAMBER LINK	
Inner stud location	2 - Middle
Inner stud spacers	1 mm
Outer stud location	A - Inside
Caster	30 deg - Kick-up: 25 / Block insert: +5
Ride height	19 mm
SHOCKS	
Arm mounting hole	C - Outside
Tower mounting hole	2 - Middle
STEERING LINK	
Inner stud spacers	0 mm
Outer stud spacers	0 mm
Steering plate / arm	Kit
Steering stop spacers	0 mm
Toe	0 degrees
Tower	Gull-wing
Wheel hex	5 mm
Wheelbase (hub carrier spacers)	Long (forward)

REAR SUSPENSION

Anti-roll bar	None
Axle height (hub insert)	+3 mm (0/3 down)
C mount	Aluminum
C mount inserts	0.5 out
Camber	-1 degrees
CAMBER LINK	
Hub insert / stud location	3 holes down / C - Middle down
Inner stud location	1 - Inside
Inner stud spacers	3 mm
D mount	Aluminum
D mount inserts	0 - center
Hub	Plastic
Ride height	19 mm
Shock location	Front of arm
SHOCKS	
Arm mounting hole	A - Inside
Tower mounting hole	2 - Middle
Wheel hex	7mm
Wheelbase (hub spacers)	Long (back)

BODY & CHASSIS

	FRONT	REAR
Wing	–	Kit
Battery position		Front hole / 5
Body		Kit
Rear wing angle		6 degrees
WEIGHT		
Electronics plate		0 g
Servo		0 g

SHOCKS

	FRONT	REAR
Bodies	Kit	Kit
Cup offset	5 mm	0 mm
Eyelet length	Long	Short
Limiters (internal)	2	0
Oil weight	37.5 wt	30 wt
Pistons	2 x 1.6mm FT v2	2 x 1.8mm FT v2
Shafts	v2 3x21mm TiN	v2 3x27.5mm TiN
Springs	v1 Orange	v1 Blue
Stroke	20 mm	28 mm
Shock oil brand	Flash Point	

DRIVETRAIN

Clutch pads	Kit
Clutch type	Slipper
Differential fluid	4,000 cst
Differential type	Gear
Driveshafts	65mm
Spur	78 teeth
Transmission gears	3
Transmission orientation	Laydown