Tekno SCT410.3

Setup: My Base Setup for RC3 · Matt Odle · May 27, 2023

so dialed
Open/save in RC Setup App →

Scan to open in the app

EVENT	
Event	Club race

TRACK	
Track	Rc3
Type	Outdoor hard-packed
Grip / moisture	Medium / Wet/Dry
Surface / layout	Medium/Bumpy / Medium
Air temp	80°F (27°C)

FRONT SUSPENSION

A mount	Composite
A mount inserts	0 - center
Anti-roll bar	2.8 mm
B mount	Composite
B mount inserts	1 down
Camber	-2 degrees
CAMBER LINK	
Inner stud location	2 - Inside middle
Outer stud location	A - Inside
Kick-up angle	11 degrees
Ride height	23 mm
Servo saver tightness	3 turns from full tight
Shock length	107 mm
SHOCKS	
Arm mounting hole	B - Outside
Tower mounting hole	4 - Inside
STEERING LINK	
Inner stud location	Middle
Inner stud spacers	Over 0 / under 4
Outer stud spacers	Over 2 / under 2
Sweep	0 degrees
Toe	+0.5 degrees
Tower	Kit
Track: wheel hexes	Lightened steel mm

NOTES Droop -107mm (max)

ELECTRONICS

Battery brand	Gens Ace
Battery capacity	8000 mAh
Battery model	Redline lihv
ESC brand	Hobbywing
ESC model	SCT 10 ezrun pro
Motor brand	Hobbywing
Motor Kv constant	4300 Kv
Radio brand	Spektrum

REAR SUSPENSION

Anti-roll bar	2.4 mm
C mount	Composite
C mount inserts	1 down
Camber	-2 degrees
CAMBER LINK	
Inner stud location	4 - Outside top
Outer stud location	B - Middle
D mount	Composite
D mount inserts	1 down and in
Ride height	25 mm
Shock length	121 mm
SHOCKS	
Arm mounting hole	A - Inside
Tower mounting hole	2 - Middle-out
Toe	-2 degrees
Tower	Kit
Track: wheel hexes	Lightened steel
Wheelbase: hub spacers	Front 2mm / rear 3mm

NOTES Droop 122mm (max)

TIRES

	FRONT	REAR
Tire brand / type	Proline Hole shot m3	Proline holeshot
Tire compound	M3	M3
Wheel brand / type	Jconcepts hazard w/3mm offset	Jconcepts hazard w/3mm offset

SHOCKS

	FRONT	REAR
Caps	Composite	Composite
Oil weight	400 cst	200 cst
Pistons	10 x 1.2mm	10 x 1.2mm
Rebound	25 %	25 %
Shafts	Steel	Steel
Shock type	Bladder	Bladder
Springs	Yellow	Black
Shock oil brand	Tekno	

DIFFERENTIALS

	FRONT	REAR
Diff fluid	7,000 cst	5,000 cst
Center diff fluid	7,000 cst	

DRIVETRAIN

Drive ratio - internal	4
Pinion	16 teeth
Spur	44 teeth

BODY & CHASSIS

Body mount - front	10mm offset / 15 degree
Body mount - front height	1 - top
Body mount - rear	0mm offset / 15 degrees
Body mount - rear height	2
Brace - front	Kit
Brace - rear	Kit
Center diff brace	Kit
Center diff mount	Composite