AE RC10 T6.1

Setup: Fastlane setup - base · Alexander Richards (Me, myself, and I) · Jul 8, 2023

so dialed
Open/save in RC Setup App →

Scan to open in the app

EVENT

Event	Base

TRACK

Track	Fastlane Raceway
Type	Indoor hard-packed
Grip / moisture	High/Medium / Dry
Surface / layout	Medium / Tight/Medium
Air temp	70°F (21°C)
Track temp	60°F (16°C)

FRONT SUSPENSION

Anti-roll bar	None
Arms	Kit
Axle height	1 mm
Bulkhead	Aluminum Factory Team
Camber	-1 degrees
CAMBER LINK	
Inner stud location	2 - Middle
Inner stud spacers	1 mm
Outer stud location	A - Inside
Caster	30 deg - Kick-up: 25 / Block insert: +5
Ride height	29 mm
SHOCKS	
Arm mounting hole	B - Middle
Tower mounting hole	2 - Middle
STEERING LINK	
Inner stud spacers	1 mm
Outer stud spacers	0 mm
Steering plate / arm	Kit
Steering stop spacers	1 mm
Toe	0 degrees
Tower	Kit
Track: wheel hexes	8.5 mm
Trail	4 mm
Wheelbase: hub carrier spacers	Long (forward)

ELECTRONICS

Motor wind	7.5 turns

REAR SUSPENSION

Anti-roll bar	None
Arms	Kit
Axle height: hub insert	0 (0/3 up)
C mount	Aluminum
C mount inserts	1 in
Camber	-1 degrees
CAMBER LINK	
Inner stud location	3 - Outside
Inner stud spacers	0 mm
Outer stud location / hub insert	3 holes down / D - Outside up
Outer stud spacers	0
D mount	Aluminum
D mount inserts	1 down
Differential height	0 mm
Hub	Aluminum FT
Ride height	27 mm
Shock location	Back of arm
SHOCKS	
Arm mounting hole	B - Middle-in
Tower mounting hole	2 - Middle
Tower	Kit
Track: wheel hexes	8.5mm
Wheelbase: hub spacers	Middle

BODY & CHASSIS

Battery position	Front hole / 2
Body	Pro-Line Enforcer
Screws & turnbuckles	3.5mm lunsford TB
WEIGHT	
Chassis	0g
Electronics plate	0 g
Servo	0 g

SHOCKS

	FRONT	REAR
Bodies	v2 12x27.5mm	v2 12x36mm
Cup offset	5 mm	5 mm
Eyelet length	Long	Long
Limiters (inner/outer)	2 / 0 mm	1 / 0 mm
Oil weight	35 wt	30 wt
Pistons	2 x 1.6 VRP	2 x 1.7 VRP
Shafts	3x27.5mm v2 Ti-N	3x35mm v2 Ti-N
Springs	54mm Gray - stiffest	72mm White
Stroke	26.5 mm	35 mm
Shock oil brand	Team Associated	

DRIVETRAIN

Clutch pads	Kit
Clutch type	Slipper
Differential type	Ball
Drive ratio - internal	2.6
Driveshafts	91mm
Pinion	23 teeth
Spur	81 teeth
Transmission gears	3
Transmission orientation	Layback

TIRES

	FRONT	REAR
Tire brand / type	ProLine Electron MC	ProLine Electron MC
Tire compound	MC (clay)	MC (clay)
Tire insert	Closed-cell	Closed-cell
Tire prep	Liquid Wrench	Liquid Wrench
Wheel brand / type	JC Mono	JC Mono