AE RC10 T6.2

Setup: My Base Setup · Todd Garner · Dec 18, 2022

so dialed
Open/save in RC Setup App →

Scan to open in the app

EVENT	
Event	Afternoon bash

TRACK	
Track	Street in front of my house
Type	Outdoor asphalt
Grip / moisture	Medium / Dry
Surface / layout	Medium / Open
Air temp	60°F (16°C)
Track temp	60°F (16°C)

FRONT SUSPENSION

ACKERMANN	
Inner steering stud spacers	1 mm
Steering block arm	+1mm
Anti-roll bar	Gray 1.3mm
Arms	Carbon fiber
Axle height	1 mm
Bulkhead	Black Steel AE 30g
Bumpsteer: outer steering stud spacers	1 mm
Camber	-1 degrees
CAMBER LINK	
Inner stud location	2 - Middle
Inner stud spacers	1 mm
Outer stud location	A - Inside
Caster	30 deg - Kick-up: 25 / Block insert: +5
Ride height	27 mm
SHOCKS	
Arm mounting hole	B - Outside
Tower mounting hole	3 - Outside
Steering stop spacers	0 mm
Toe	0 degrees
Tower	Kit
Track: wheel hexes	8.5 mm
Trail: steering blocks	4 mm
Wheelbase: hub spacers - F/R	0 / 1 mm

ELECTRONICS

Battery capacity	6000 mAh
ESC brand	Hobbywing
ESC model	G2
Motor brand	Hobbywing
Motor model	3652
Radio brand	Futaba
Radio model	3PV
Receiver brand	Futaba
Receiver model	203SB
Servo brand	Savox
Servo model	Black Super Speed

REAR SUSPENSION

Anti-roll bar	Blue 1.3mm
Arms	Carbon fiber
Axle height: hub inserts	0 (0/3 up)
C mount	Exotek 23gm
C mount inserts	0 center
Camber	-1 degrees
CAMBER LINK	
Inner stud location	1 - Inside
Inner stud spacers	2 mm
Outer stud mount spacers	2 mm
Outer stud spacers	2
D mount	Aluminum
D mount inserts	0 center
Differential height	3 mm
Hubs	Aluminum FT
Ride height	26 mm
Shock location	Back of arm
SHOCKS	
Arm mounting hole	A - Inside
Tower mounting hole	3 - Outside
Tower	Kit
Track: wheel hexes	8.5mm
WHEELBASE	
Arm spacers - F/R	0 / 2 mm
Hub spacers - F/R	1 / 1 mm

TIRES

	FRONT	REAR
Tire brand / type	Proline trencher 2.2	Proline trencher 2.2
Tire compound	M2	M2
Tire insert	Hard	Soft
Wheel brand / type	Schumacher black stadium truck	Schumacher black stadium truck

SHOCKS

	FRONT	REAR
Cup offset	5 mm	5 mm
Eyelet length	Long	Long
Limiters - int/ext	0 / 0 mm	0 / 0 mm
Oil weight	30 wt	30 wt
Pistons	2 x 1.6mm FT v2	2 x 1.7mm FT v2
Springs	4.45lb Grey	2.40lb White
Stroke	27.5 mm	35 mm
Shock oil brand	Team Associated	

DRIVETRAIN

Clutch pads	2
Clutch type	Slipper
Differential type	Ball
Drive ratio - internal	2.60
Driveshafts	91mm CVD
Pinion	24 teeth
Spur	81 teeth
Transmission gears	3
Transmission orientation	Laydown

BODY & CHASSIS

Battery position	Front hole / 5
Body	T.6.1
FLEX	
Chassis	T6.1
Chassis side rails	Standard
Rear wing	T.6.1