AE RC10 T6.2

Setup: Rc Madness T6.2 · Aydan Manchanda (Team Associated) · Jan 7, 2023

so dialed
Open/save in RC Setup App →

Scan to open in the app

EVENT	
Event	Club Race

TRACK	
Track	RC Madness
Type	Indoor carpet
Grip / moisture	Medium / Dry
Surface / layout	Smooth / Tight
Air temp	65°F (18°C)
Track temp	55°F (13°C)

RESULTS	
Race type	Main

FRONT SUSPENSION

ACKERMANN	
Inner steering stud spacers	2 mm
Steering block arm	+1mm
Anti-roll bar	Gray 1.3mm
Arms	Kit
Axle height	1 mm
Bulkhead	Steel
Bumpsteer: outer steering stud spacers	0 mm
Camber	-1 degrees
CAMBER LINK	
Inner stud location	2 - Middle
Inner stud spacers	1 mm
Outer stud location	A - Inside
Caster	30 deg - Kick-up: 25 / Block insert: +5
Ride height	22 mm
SHOCKS	
Arm mounting hole	A - Inside
Tower mounting hole	2 - Middle
Steering stop spacers	0 mm
Toe	0 degrees
Tower	Kit
Track: wheel hexes	8.5 mm
Trail: steering blocks	4 mm
Wheelbase: hub spacers - F/R	0 / 1 mm

ELECTRONICS

Battery brand	Reedy
Battery capacity	4800 mAh
Battery model	4800 LCG
ESC brand	Reedy
ESC model	510R
Motor brand	Reedy
Motor wind	10.5 turns
Radio brand	Sanwa/Airtronics
Servo brand	Reedy

REAR SUSPENSION

Anti-roll bar	White 1.1mm
Arms	Kit
Axle height: hub inserts	0 (0/3 up)
C mount	Aluminum
C mount inserts	1 down
Camber	-1 degrees
CAMBER LINK	
Inner stud location	2 - Middle
Inner stud spacers	0 mm
Outer stud mount spacers	2 mm
Outer stud spacers	2
D mount	Aluminum
D mount inserts	1 in
Differential height	2 mm
Hubs	Plastic
Ride height	22 mm
Shock location	Front of arm
SHOCKS	
Arm mounting hole	A - Inside
Tower mounting hole	3 - Outside
Tower	Kit
Track: wheel hexes	8.5mm
WHEELBASE	
Arm spacers - F/R	0 / 2 mm
Hub spacers - F/R	1 / 1 mm

TIRES

	FRONT	REAR
Tire brand / type	JC Swagger	JC Pin Down

SHOCKS

	FRONT	REAR
Cup offset	5 mm	5 mm
Eyelet length	Long	Long
Limiters - int/ext	0 / 0 mm	0 / 0 mm
Oil weight	42.5 wt	32.5 wt
Pistons	2 x 1.6mm FT v2	2 x 1.7mm FT v2
Springs	Orange buggy front	Yellow
Stroke	27.5 mm	35 mm
Shock oil brand	Team Associated	

DRIVETRAIN

Clutch pads	2
Clutch type	Slipper
Differential type	Ball
Drive ratio - internal	2.60
Driveshafts	91mm CVD
Spur	81 teeth
Transmission gears	3
Transmission orientation	Laydown

BODY & CHASSIS

Battery position	Front hole / 4
Body	T.6.1
FLEX	
Chassis	T6.1
Chassis side rails	Standard
Rear wing	T.6.1