TLR Mini-T 2.0

Setup: Backyard track/ hard red clay · DavidW · Mar 13, 2023

so dialed
Open/save in RC Setup App →

Scan to open in the app

EVENT

Event	Practice

TRACK

Track	Backyard
Type	Outdoor clay
Grip / moisture	Low / Dry
Surface / layout	Blown-out / Tight/Medium
Air temp	75°F (24°C)
Track temp	80°F (27°C)

FRONT SUSPENSION

Camber	-1 degrees
CAMBER LINK	
Inner location	Outside
Inner spacers	0 mm
Outer spacers	1 mm
Caster block	Standard
Ride height	15 mm
SHOCKS	
Arm mounting hole	Inside
Tower mounting hole	Upper inside, aluminum 5 hole tower w/ 3 upper 2 lower
STEERING LINK	
Inner stud spacers	0 mm
Outer stud spacers	0 mm
Toe	+1 degrees
Track: wheel hexes	Standard mm

NOTES Max ride height w/ keeping some droop

TIRES

	FRONT	REAR
Tire brand / type	ProLine Hole shot	ProLine Hole shot
Tire insert	PL assembled	Flipped
Wheel brand / type	PL assembled	TLR

NOTES Fronts are worn slick

REAR SUSPENSION

Camber	-0.5 degrees
CAMBER LINK	
Inner spacers	0 mm
Outer location	Inside
Outer stud spacers	1 mm
Ride height	20 mm
SHOCKS	
Arm mounting hole	Outside
Tower mounting hole	Lower inside, aluminum 5 hole tower w/ 3 upper 2 lower
Track: wheel hexes	Standard

NOTES Max ride height w/ some droop

BODY & CHASSIS

Body	Jconcepts Finisher
Rear wing	None
Weight balance (F/R)	36 / 64
Weight: total	616 g

ELECTRONICS

Battery brand	Dynamite
Battery C rating	20 C
Battery capacity	800 mAh
Battery model	Reaction2
ESC brand	Horizon
ESC model	6000kv 2n1
ESC settings	OEM
Motor brand	Dynamite
Radio brand	RadioLink
Radio EPA steering	100 %
Radio EPA throttle	58 %
Radio model	RC6GS v3
Receiver brand	RadioLink
Receiver model	R4FGM
Servo brand	EMax
Servo model	ES08MDII

NOTES ThEpa:58%
StExp: -40%
ThExp: -40%
BkExp: -40%
ThSpd: 2 L:100 H:85 Tgp1: 60
Accel: Fwd:10%
D/R: ST: 60%
Gyro: 18%

SHOCKS

	FRONT	REAR
Bodies	Standard	Standard
Limiters - Int/ext	0 / 0	0 / 0
Oil weight	5w20	5w20
Pistons	Custom, drilled out OEM	Custom, drilled out OEM
Springs	Black	Black
Shock oil brand	Pnzl	

DRIVETRAIN

Clutch pads	Kit
Clutch type	Slipper
Differential fluid	Spool cst
Differential fluid brand	Hot Racing
Differential type	Gear
Driveshafts	Dogbones
Pinion	15
Spur	60 teeth

NOTES Spooled for loose track surface