SWORKz S14-3/D

Setup: RcPark 6mik hiver · Mar 6, 2023

so dialed
Open/save in RC Setup App →

Scan to open in the app

TRACK

Track	Rc Park
Type	Indoor carpet
Grip / moisture	Medium / Dusty
Surface / layout	Medium
Air temp	7.5°C (46°F)
Track temp	7.5°C (46°F)

FRONT SUSPENSION

Anti-roll bar	2.0 mm
Anti-roll bar end gap	2 mm
Arms	Kit
C-hub (caster)	11 deg Aluminum (#334043L/R)
Camber	-2 degrees
CAMBER LINKS	
Inner mount location	1 - Top
Outer stud spacers	3 mm
FF mount inserts	0 center
FR mount inserts	0 center
Ride height	14 mm
SHOCKS	
Arm mounting hole	A - Inside
Tower mounting hole	3 - Outside
STEERING LINK	
Inner stud location	1 - Front
Inner stud spacers	2.0 mm
Outer stud spacers	1.5 mm
Toe	-0.5 degrees
Track: wheel hexes	5.7
Wheelbase: arm spacers - F/R	0 / 2 mm

ELECTRONICS

Battery brand	Intellect Pioneering
Battery capacity	4200 mAh
Battery model	LCG
ESC model	Skyrc Toro 160
ESC settings	Blinky
Motor brand	Surpass
Motor timing	48 degrees
Motor wind	10.5 turns
Radio model	Sanwa exzesX
Steering servo brand	Power HD
Steering servo model	B4

NOTES 6A

REAR SUSPENSION

Anti-roll bar	2.0 mm
Anti-roll bar end gap	0 mm
Arms	Kit
Camber	-2 degrees
CAMBER LINK	
Inner stud location	2 - Inside middle
Outer stud location	B - Middle
Hubs	Kit
RF mount inserts	1 up and out
Ride height	15
RR mount inserts	1 up and out
SHOCKS	
Arm mounting hole	A - Inside
Tower mounting hole	3 - Outside
Track: wheel hexes	4.7 mm
Wheelbase: hub spacers - F/R	1 / 0 mm

NOTES 0.5 mm spacer cavalieri insert roll center box

TIRES

	FRONT	REAR
Tire brand / type	6mik wazabi silver	6mik wazabi silver
Tire insert	Open-cell	Open-cell
Wheel brand / type	Sworkz	Sworkz

SHOCKS

	FRONT	REAR
Oil weight	700 cst	700 cst
Pistons	2 x 1.6mm	2 x 1.7mm
Shock length	86 mm	98 mm
Springs	S4-Dot 43mm	L3-Dot 57mm
Shock oil brand	6MIK	

DIFFERENTIALS

	FRONT	REAR
Diff fluid	12,000 cst	7,000 cst
Diff fluid brand	SWORKz	
Drive type	Slipper clutch	

DRIVETRAIN

Drive ratio - internal	2.471
Pinion	23 teeth
Spur	78 teeth

BODY & CHASSIS

	FRONT	REAR
Wing	–	Kit
Battery position	Front	
Body	Kit	
FLEX		
Chassis brace - front	Standard	
Chassis brace - rear	Standard	
Side guards	Standard	
Rear wing mount position	Low	
Weight balance (F/R)	50 / 50	

NOTES Long châssis +7mm