# AE RC10 T6.2

Setup: Gt6.2 Fastlane base · Alexander Richards (Me, myself, and I) · Jul 1, 2023

so dialed
Open/save in RC Setup App →

Scan to open in the app

| EVENT | |
|---|---|
| Event | All |

| TRACK | |
|---|---|
| Track | Fastlane Raceway |
| Type | Outdoor hard-packed |
| Grip / moisture | Medium / Dry |
| Surface / layout | Medium / Medium |

## FRONT SUSPENSION

| | |
|---|---|
| **ACKERMANN** | |
| Inner steering stud spacers | 0.5 mm |
| Steering block arm | +1mm |
| Anti-roll bar | None |
| Arms | Flat t6.1 |
| Axle height | 1 mm |
| Bulkhead | Aluminum Factory Team |
| Bumpsteer: outer steering stud spacers | 2 mm |
| Camber | -1 degrees |
| **CAMBER LINK** | |
| Inner stud location | 2 - Middle |
| Inner stud spacers | 3 mm |
| Outer stud location | A - Inside |
| Caster | 25 deg - Kick-up: 30 / Block insert: -5 |
| Ride height | 27 mm |
| **SHOCKS** | |
| Arm mounting hole | Middle |
| Tower mounting hole | 2 - Middle |
| Steering stop spacers | 0 mm |
| Toe | 0 degrees |
| Tower | PSM 5MM |
| Track: wheel hexes | 8.5 mm |
| Trail: steering blocks | 4 mm |
| Wheelbase: hub spacers - F/R | 0 / 1 mm |

## REAR SUSPENSION

| | |
|---|---|
| Anti-roll bar | None |
| Arms | T6.1 |
| Axle height: hub inserts | 0 (0/3 up) |
| C mount | Brass 23g |
| C mount inserts | 1 up and in |
| Camber | -1 degrees |
| **CAMBER LINK** | |
| Inner stud location | 2 - Middle |
| Inner stud spacers | 0.5 mm |
| Outer stud mount spacers | 1 mm |
| Outer stud spacers | 1 |
| D mount | Aluminum |
| D mount inserts | 1 down and out |
| Differential height | 0 mm |
| Hubs | Aluminum FT |
| Ride height | 26 mm |
| Shock location | Back of arm |
| **SHOCKS** | |
| Arm mounting hole | A - Inside |
| Tower mounting hole | 1 - Inside |
| Tower | PSM 5mm |
| Track: wheel hexes | 8.5mm |
| **WHEELBASE** | |
| Arm spacers - F/R | 0 / 2 mm |
| Hub spacers - F/R | 2\0 mm |

## TIRES

| | FRONT | REAR |
|---|---|---|
| Tire brand / type | Jconcepts Sprinters | Jconcepts Sprinters |
| Tire compound | Green < 80deg Blue >80 deg | Green < 80deg Blue >80 deg |
| Tire insert | Jcon grey, 2 holes punched in rib | Jcon grey, 2 holes punched in rib |
| Wheel brand / type | Jcon Mono | Jcon Mono |

## SHOCKS

| | FRONT | REAR |
|---|---|---|
| Cup offset | 5 mm | 5 mm |
| Eyelet length | Long | Long |
| Limiters - int/ext | 0 / 0 mm | 0 / 0 mm |
| Oil weight | 37.5 wt | 30 wt |
| Pistons | 2x1.6 VRP | 2x1.7 VRP |
| Springs | 4.45lb Grey | 2.40lb White |
| Stroke | 27.5 mm | 35 mm |

Shock oil brand: Team Associated

## DRIVETRAIN

| | |
|---|---|
| Clutch pads | 2 |
| Clutch type | Slipper |
| Differential type | Ball |
| Drive ratio - internal | 2.60 |
| Driveshafts | 91mm CVD |
| Pinion | 15 teeth |
| Spur | 64 teeth |
| Transmission gears | 3 |
| Transmission orientation | Layback |

## BODY & CHASSIS

| | |
|---|---|
| Battery position | Rear hole / 4 |
| Body | Jcon 0388 Finnisher |
| **FLEX** | |
| Chassis | T6.1 |
| Chassis side rails | Standard |
| Rear wing | T.6.1 |
| Weight: total | 1571g |