SNRC R3-G/C/Pro

Setup: R3 Pro Medium/High Grip · Feb 9, 2025

so dialed
Open/save in RC Setup App →

Scan to open in the app

TRACK

Track	Tyne Met
Type	Indoor carpet
Grip / moisture	High / Dry
Surface / layout	Smooth / Medium

FRONT SUSPENSION

ACKERMANN	
Inner steering link shims	0 mm
Outer steering link location	Back
Anti-roll bar	1.6mm
Arms	Standard
Bump steer: outer steering link shims	0 mm
CAMBER LINK	
Inner location	Back inside
Inner shims	2 mm
Outer shims	0 mm
Caster	4 degrees
FF mount	Standard
FF mount inserts	0 mm
FR mount	Standard
FR mount inserts	0 mm
Hubs & steering blocks	Composite 8-deg block
Ride height	5.0 mm
Shocks: tower mounts	Middle
Steering bell crank	Aluminum
Steering: bell crank arm shims	1 mm
Tower	Graphite
Track: wheel hexes	5mm
WHEELBASE	
Arm shims - F/R	1.5 / 0 mm
Hub shims - F/R	1.5 / 1 mm

REAR SUSPENSION

Anti-roll bar	1.2mm
Anti-roll bar arm mounts	Middle
Arms	Standard
CAMBER LINK	
Inner location	Front outside
Inner shims	2 mm
Outer location	Inside
Outer shims	2 mm
RF mount	Standard
RF mount inserts	0 mm
Ride height	5.0 mm
RR mount	Standard
RR mount inserts	0 mm
Shocks: tower mounts	Middle
Tower	Graphite
Track: wheel hexes	5mm
Uprights	Composite
Wheelbase: arm shims - F/R	2 / 0 mm

BODY & CHASSIS

Body	Montec Imola
Body position	Central
Bumper	Foam
FLEX	
Chassis	2.0mm Graphite
Upper deck - front	Graphite
Upper deck - rear	Graphite

SHOCKS

	FRONT	REAR
Oil weight	400 cst	400 cst
Pistons	2-hole	2-hole
Spring cups	-1mm	-1mm
Springs	3.5kg Silver	3.5kg Silver
Shock oil brand	CORE	

DIFFERENTIALS

	FRONT	REAR
Diff fluid mass	1.3 g	1.3 g
Diff fluid	–	4,000 cst
Diff fluid brand	CORE	
Front diff type	Spool	
Rear diff gear type	Plastic	

DRIVETRAIN

Drive ratio - internal	1.9
Driveshafts - front	38mm 3.0pin CVD
Driveshafts - rear	46mm 2.0pin S2 CVD
Front drive type	Spool
Spur	78 teeth

TIRES

	FRONT	REAR
Tire brand / type	C	Contact
Tire compound	A30	A30