Tekno ET410.2

Setup: Base Setup · RustyUs · Sep 13, 2026

so dialed
Open/save in RC Setup App →

Scan to open in the app

TRACK

Type	Outdoor hard-packed
Grip / moisture	Low/Medium / Dry
Surface / layout	Bumpy/Rutted / Medium
Air temp	80°F (27°C)
Track temp	80°F (27°C)

FRONT SUSPENSION

A mount inserts	0 center
Anti-roll bar	None mm
B mount inserts	0 center
Camber	-2 degrees
CAMBER LINK	
Inner stud location	2 - Middle
Outer stud location	B - Outside
Outer stud spacers	0
Caster	18 degrees
Ride height	Bones Level mm
Shock length	87 mm
SHOCKS	
Arm mounting hole	A - Inside
Tower mounting hole	2 - Middle
Steering arm	D - 19mm
Steering arm spacers	2 mm
STEERING LINK	
Inner stud spacers	4
Outer stud spacers	4
Steering stop spacers	0
Toe	+1 degrees
Tower	Kit
Track: wheel hexes	Lightened steel mm
Wheelbase: arm spacers	Front 2.0mm / rear 0.0mm (short)

ELECTRONICS

Battery brand	CNHL
Battery C rating	120
Battery capacity	4900 mAh
ESC brand	Hobbywing
ESC model	Max10 G2 80A
Motor brand	Hobbywing
Motor Kv constant	4100 Kv
Motor model	G3
Radio brand	Flysky
Radio EPA steering	100 %
Radio EPA throttle	90 %
Radio model	Noble NB4
Receiver brand	Flysky
Receiver model	FGr4S v2
Servo brand	Team Associated
Servo model	DS1015

REAR SUSPENSION

Anti-roll bar	None mm
Axle height: hub inserts	3 - High
C mount inserts	0 center
Camber	-2 degrees
CAMBER LINK	
Inner stud location	2 - Mid-top
Outer stud location	B / arrow down
D mount inserts	0 center
Ride height	Just Below Bones Level mm
Shock length	107 mm
SHOCKS	
Arm mounting hole	A - Inside
Tower mounting hole	2 - Middle
Toe	-1.5 degrees
Tower	Kit
Track: wheel hexes	Lightened steel
WHEELBASE	
Arm spacers	Front 0.0mm / rear 2.0mm (short)
Hub spacers	Front 1mm / rear 1mm

BODY & CHASSIS

Body	Kit
Center diff brace	Kit
Center diff mount	Kit
Rear brace	Short and Long
Rear wing	VR-Pro Buggy
Rear wing angle	6 degrees (flat) degrees
Rear wing position	4
Rear wing spacers	10 mm

SHOCKS

	FRONT	REAR
Caps	Aluminum Emulsion	Aluminum Emulsion
Limiters (internal)	0	0
Oil weight	300 cst	300 cst
Pistons	5 x 1.1mm	5 x 1.2mm
Rebound	0 %	0 %
Shafts	Kit	Kit
Shock type	Emulsion	Emulsion
Springs	Green 3.5 SC10 4x4	White 2.5 SC10 4x4
Stroke	27 mm	37 mm
Shock oil brand	PT RC	

DIFFERENTIALS

	FRONT	REAR
Diff fluid	30,000 cst	15,000 cst
Center diff fluid	30,000 cst	

DRIVETRAIN

Drive ratio - internal	4
Spur	53 teeth

TIRES

	FRONT	REAR
Tire brand / type	Step Pins	Step Pins
Tire compound	Soft	Soft
Tire insert	Open-cell	Open-cell
Wheel brand / type	Team Associated	Team Associated

ESC SETTINGS

BRAKE	
Drag	0 %
Strength	75 max
Throttle: Initial strength	1 %