1RC Late Model 1/18

Setup: 2023 Kenman Classic at RC Underground WI · George Mari · Jul 14, 2025

so dialed
Open/save in RC Setup App →

Scan to open in the app

EVENT

Event	Kenman Classic 2023

TRACK

Track	RC Underground WI Foam Oval
Type	Indoor rcp foam
Grip / moisture	High / Dry
Surface / layout	Smooth / Tight

RESULTS

Race type	Main
Race number	A
Finish	1st

FRONT SUSPENSION

LF caster	**0 degrees**
RF caster	**-2 degrees**
Servo arm hole	**Upper**
Servo arm type	**Servo saver**

NOTES Removed stock front suspension springs and placed short springs on front shocks.

ELECTRONICS

Battery brand/model	**Turnigy**
Battery capacity	**300 mAh**
Battery cells	**2**
Battery type	**LiPo**
ESC	**1RC**
Motor brand/model	**1RC**
Motor Kv constant	**8,700 Kv**
Radio	**Flysky GT5**
Radio dual-rate	**60 %**
Receiver	**Flysky GT2E**
Servo	**1RC**

NOTES Steering exponential 15%

REAR SUSPENSION

RR hex offset	**2mm**

NOTES Adjustable radius rod on left rear, 2 turns shorter than stock.

BODY & CHASSIS

Motor heatsink	**Yes**

TIRES

LF tire compound	**Standard**
LR tire compound	**Standard**
RF tire compound	**Standard**
RR tire compound	**Standard**

NOTES 1/8-inch wide strip of super glue on outer edge of right front tire. Also super glue on entire outside face of both front tires.

ESC SETTINGS

BRAKE	
Drag force	**20 %**
Initial force	**0 %**
Max force	**50 %**
Low voltage cut-off	**Disabled**
Max reverse force	**50 %**
Neutral range	**9 %**
Overheat warning	**Enabled**
Running mode	**FWD / Brake**
Start mode / punch level	**9**
Timing	**7.5 degrees**

SHOCKS

LF body	**Plastic**
LF grease	**AE Greenn Slime**
LF o-ring	**Clear**
LF pre-load	**0 mm**
LF spring	**Short Medium**
LF stroke	**6.35 mm**
LR body	**Plastic**
LR grease	**AE Green Slime**
LR o-ring	**Clear**
LR pre-load	**0 mm**
LR spring	**Short Hard**
LR stroke	**6.35 mm**
RF body	**Plastic**
RF grease	**AE Green Slime**
RF o-ring	**Clear**
RF pre-load	**0 mm**
RF spring	**Short Hard**
RF stroke	**6.35 mm**
RR body	**Plastic**
RR grease	**AE Green Slime**
RR o-ring	**Clear**
RR pre-load	**0 mm**
RR spring	**Short Medium**
RR stroke	**6.35 mm**
Shock caps	**Drilled**
Shock oil brand	**Team Associated**