SETUP SHEET

SRX2 gen3

SERPENT

More: sodialed.com/setups

DRIVER, TRACK AND RESULTS

DRIVER	RC Zone PR	COUNTRY		**WEATHER**	AIR 29C/85F	TRACK 24C/75F	Moisture: Dry
RACE		June 21, 2025	QUALY POS.	STARTING POS.	P: 6	FINAL POS.	Best: 15.2
TRACK	Rc Zone Carpet	**TYPE**	Indoor carpet	**STYLE**	☐ TIGHT ☐ MEDIUM ☐ OPEN ☐		Tight
SURFACE	**GRIP** ☐ LOW ☐ MEDIUM ☐ HIGH ☐		High	**CONDITION**	☐ SMOOTH ☐ ROUGH ☐		Smooth
Setup: My Base Setup				Open in So Dialed App			

SHOCK ABSORBERS

FRONT		REAR
40 wt	OIL	35 wt
V1 purple ae	SPRINGS	Astro 2.1 lb Blue
0	REBOUND	0
Int: 1.25 Ext: 0	LIMITERS	Int: 1.25 Ext: 0
2 x 1.6mm	PISTONS	2 x 1.7mm
Oil brand: Team Associated		
☐ SHORT ◉ LONG SPRING BUCKETS		☐ SHORT ◉ LONG
☐ BLADDER ◉ EMULSION	SEAL TYPE	☐ BLADDER ◉ EMULSION

ANTI-ROLL BARS

☐ FRONT	☐ REAR
Front: 1.2	Rear: 1.1mm 1 stripe

REAR DIFFERENTIAL

◉ BALL DIFFERENTIAL

☐ GEAR DIFF 30,000 cst

DIFF HEIGHT 0

GEARING

PINION Teeth

SPUR GEAR 78 Teeth

ELECTRONICS

BATTERY

BRAND CAPACITY mAh

MOTOR

BRAND TYPE TIMING

ESC

BRAND TYPE

AERODYNAMIC CONFIGURATION

BODY Lfr

REAR WING 6.5" 1.5mm

REAR WING WIDTH REAR WING LIP mm

RR WING ANGLE ☐ 0° ☐ 2° ◉ 4° ☐ 6° ☐ 8° MOUNT ☐ STD ☐ LOW

FRONT WING ☐ YES ☐ NO TYPE

TIRES

FRONT	Controlled Tire ☐	REAR
	MAKE	
	TYPE	
	COMPOUND	
	INSERTS	
Serpent	WHEELS	Serpent
	ADDITIVE	

FRONT / REAR

CASTER BLOCK INSERTS ◉ + ☐ - ; ☐ 0 ☐ 2.5 ◉ 5

3 - Mid-out

SHOCK POSITION 1 2 3

SHOCKS POSITION ☐ REAR ◉ FRONT

Axle height: Top 1 mm/bottom 2mm

SHIMS 0 mm | **SHIMS** 0 mm | **SHIMS** 0 mm | **SHIMS** 0.5 mm | **SHIMS** 2.5 mm

AXLE SPACER ◉ YES ☐ NO

WHEEL HEX +1mm

FRONT CAMBER -1.5

REAR CAMBER -3

RIDE HEIGHT 14 mm | **RIDE HEIGHT** 14 mm

FRONT BULKHEAD ☐ STOCK ◉ ALU ☐ BRASS

FRONT CASTER BLOCK ◉ STOCK ☐ ALU STEERING SREW ☐ YES ☐ NO

REAR WHEEL BASE Front ◉ ◉

REAR ARM ☐ LONG ◉ SHORT

FRONT ARM SRX2

TRANSMISSION Gears: 3 Layout: Gen3

REAR HUB ◉ SHORT OFFSET HUB ☐ LONG OFFSET HUB

REAR UPRIGHT INSERT AXLE HEIGHT ☐ 0 ☐ 0.5 ☐ 1 ◉ 1.5 ☐ 2 ☐ 2.5 ☐ 3 ; INSERT OFFSET -1 ◉ 0 ☐

BUMP STEER SPACER ☐ YES ☐ NO ; SHIMS 0 mm

ACKERMANN ☐ OPT.0 ☐ OPT.1 ☐ OPT.2 ◉ OPT.3 ; SHIMS 0 mm

REAR FRONT TOE BLOCK Aluminum narrow (IN / IN)

REAR REAR TOE BLOCK Aluminum narrow (IN / IN)

REAR AXLE ◉ LONG SHAFT ☐ SHORT SHAFT ; SHIMS

DRIVETRAIN DRIVESHAFT — Pin: Middle ; LENGTH 66mm SRX2

SLIPPER ◉ STOCK PLATES ☐ VENTED PLATES ; Drive type: Slipper ; DISTANCE 1.5-2mm from end of shaft

FRONT TOE 0 °

WEIGHT DISTRIBUTION CAR WEIGHT 1520 grams ; WEIGHT BIAS FR % RR %

Batt location: Mid

REAR TOE 0

REMARKS