Traxxas Slash 2WD

Setup: OnRoad Setup · Juan · Aug 16, 2023

so dialed
Open/save in RC Setup App →

Scan to open in the app

TRACK

Type	Outdoor asphalt
Grip / moisture	Medium / Dry
Surface / layout	Smooth / Tight
Air temp	17.5°C (64°F)

FRONT SUSPENSION

Anti-roll bar	None
Arms	RPM
Camber	-2 degrees
Hub carriers	Kit 30 degree
Shocks: arm mounting hole	B - Outside
Steering bellcrank	Aluminum
Steering blocks	Kit
Toe	+0.5 degrees
Tower	Kit
Track: wheel hexes	12mm

BODY & CHASSIS

Battery position	Rear
Body	TRX Slash
Chassis	Low CG
Rear wing	Kit
Rear wing height	High
Weight balance - F/R	- / -

REAR SUSPENSION

Anti-roll bar	None
Arms	RPM
Camber	-2.5 degrees
Hubs	Kit

ROLL CENTER

Hub pin location	Lower
Inner camber link location	Lower
Shocks: arm mounting hole	E - Outside
Tower	Kit
Track: wheel hexes	12mm

ELECTRONICS

ESC brand	Traxxas
ESC model	Vxl-3s
Motor brand	Traxxas
Motor Kv constant	3500 Kv
Motor model	Velineon
Motor wind	12 turns
Radio brand	Spektrum
Receiver brand	Spektrum
Servo brand	Traxxas

SHOCKS

	FRONT	REAR
Bodies	Ultra long	Ultra XX-long
Limiters - internal/external	0 / 0 mm	0 / 0 mm
Oil weight	40 wt	70 wt
Pistons	3-hole	3-hole
Shafts	Kit	Kit
Springs	Kit	Kit

Shock oil brand	Team Losi

DRIVETRAIN

Differential fluid	300,000 cst
Differential type	Gear
Drive ratio - internal	2.72
Drive type	Slipper
Driveshafts	Heavy duty
Pinion	18 teeth
Slipper clutch pads	Kit
Slipper tightness	1/2 turn back from fully tight
Spur	86 teeth