Xpress EXECUTE XM1S

Setup: Adam downing LBMCC setup 1 · Adam downing (Destiny) · Dec 12, 2023

so dialed
Open/save in RC Setup App →

Scan to open in the app

EVENT

Event	Club Nights

TRACK

Track	LBMCC
Type	Indoor carpet
Grip / moisture	Medium / Dry
Surface / layout	Medium/Bumpy / Medium/Tight

FRONT SUSPENSION

ACKERMANN

Inner steering link spacers	0 mm
Outer steering stud location	1 - Outside
Anti-roll bar	1.3 mm
Arms	Medium
Bumpsteer: outer steering stud spacers	0 mm
Camber	-2 degrees

CAMBER LINK

Inner stud spacers	0 mm
Outer stud spacers	0 mm
Differential height	Low
Downstop	5 mm
FF mount	Composite
FF mount inserts	1 down
FF mount spacers	0 mm
FR mount	One-piece aluminum
FR mount inserts	1 down
FR mount spacers	0 mm
Hub carriers	Composite 4-degree
Ride height	5 mm

SHOCKS

Arm mount spacers	2.0 mm
Arm mounting hole	C - Outside
Tower mount spacers	0 mm
Tower mounting hole	3 - Outside
Steering block plates	Medium
Steering blocks	Medium
Toe	-1 degrees
Tower	Graphite
Track: wheel hexes	Aluminium 7mm
Wheelbase: arm spacers - F/R	4 / 3 mm

NOTES X eat low profile shocks, Low profile carbon tower kit

REAR SUSPENSION

Anti-roll bar	1.3 mm
Arms	Medium
Camber	-2 degrees

CAMBER LINK

Inner stud spacers	0 mm
Outer stud location	A - Inside
Outer stud spacers	0 mm
Differential height	Low
Downstop	4 mm
RF mount	Split aluminum
RF mount inserts	0 center
RF mount spacers	0 mm
Ride height	5 mm
RR mount	Aluminum
RR mount inserts	0 center
RR mount spacers	0 mm

SHOCKS

Arm mount spacers	0 mm
Arm mounting hole	D - Mid-out
Tower mount spacers	0 mm
Tower mounting hole	2 inside on low profile tower
Toe	-3 mm
Tower	Graphite
Track: wheel hexes	Aluminium 7mm
Uprights	Medium
Wheelbase: arm spacers - F/R	0 / 6 mm

NOTES X ray low profile shocks with low profile shock tower kit

TIRES

	FRONT	REAR
Additive area	Inside 50%	Full tire
Tire brand / type	Sweep	Sweep
Tire compound	25	25
Wheel brand / type	Sweep	Sweep
Tire additive - F/R	MR33	
Tire glue diameter - F/R	- / - mm	

SHOCKS

	FRONT	REAR
Bodies	Aluminium	Aluminium
Oil weight	450 cst	450 cst
Pistons	4-hole	4-hole
Rebound	0 %	–
Springs	Core RC yellow	Core RC orange
Stroke	11 mm	11 mm
Shock oil brand	XRt	

DIFFERENTIALS

	FRONT	REAR
Diff fluid	Spool cst	6,000 cst
Diff fluid mass	–	1.3 g
Front diff type	Spool	

NOTES Front spool out drives upgraded to steel and upgraded driveshafts with multi pivot points

DRIVETRAIN

Drive ratio - internal	1.9
Gear pitch	64
Pinion	47 teeth
Spur	110 teeth

BODY & CHASSIS

Body	Blitz TCn

FLEX

Chassis	FRP
Upper deck	FRP