XRAY X4 '24

Setup: GP3F #19 2024 · Roel Jongenelis (XRAY/Rcconect/LRP/PowerHD) · Feb 15, 2024

so dialed
Open/save in RC Setup App →

Scan to open in the app

EVENT

Event	GP3F #19 2024
Class	Stock expert

TRACK

Track	MRC LONGWY GP3F
Type	Indoor carpet
Grip / moisture	High / Dry
Surface / layout	Medium / Medium
Air temp	22.5°C (73°F)
Track temp	22.5°C (73°F)

RESULTS

Race type	Main
Finish	13th
Best lap	11.40 s
Average lap	11.70 s

FRONT SUSPENSION

ACKERMANN	
Inner steering link shims	0.5 mm
Steering arms	Standard
Steering plate	8mm
Anti-roll bar	1.2 mm
Arms - lower	Hard (#302182/3-H)
Arms - upper	Med (#302134/44-M)
Axle height: hub shims	1 mm
Bump steer: outer steering link shims	2 mm
Camber	-1.2 degrees
CAMBER LINK	
Inner shims	2.25 mm
Outer shims	2 mm
Caster bushings	4 degrees - 2 dot
Differential height	Low
Downstop	6 mm
FF mount shims	2.5 mm
FR mount shims	2.5 mm
Hubs	Graphite
Ride height	5.2 mm
Servo arm type	Servo horn
Servo saver shims	6.5 mm
Servo saver stud radius	20 mm
Shock tower mount screws	Both
Shocks: tower shims	2 mm
Steering lock	23 deg - 8.75mm shim
Toe out	2 degrees
TRACK	
Wheel hexes	+0mm
Wheel shims	0 mm

NOTES Home made steering lock shim

REAR SUSPENSION

Anti-roll bar	1.2 mm
Arms - lower	Hard (#303182/3-H)
Arms - upper	Med (#302134/44-M)
Axle height: hub shims	1 mm
Camber	-2 degrees
CAMBER LINK	
Inner stud shims	2 mm
Outer stud shims	2 mm
Caster bushings	3.5 degrees - 3 dot rearward
Differential height	Low
Downstop	4.2 mm
Hubs	Graphite
RF mount shims	3 mm
Ride height	5.4 mm
RR mount shims	3 mm
Shock tower mount screws	Both
SHOCKS	
Holder type	Fixed
Tower shims	2 mm
Toe gain: ARS link outer shims	1 mm
Toe in	2 degrees
TRACK	
Wheel hexes	+0mm
Wheel shims	0 mm

TIRES

	FRONT	REAR
Tire additive	HUDY RED	HUDY RED
Tire additive area	In, Mid-in, Mid-out, Out	In, Mid-in, Mid-out, Out
Tire additive timing	3 min	8 min
Tire additive wipe-off time	2 min before start min	2 min before start min
Tire brand / type	Rush	Rush
Tire warmer temp	0 degrees	0 degrees
Tire warmer time	0 min	0 min
Wheel brand / type	Spoke wheel	Spoke wheel

SHOCKS

	FRONT	REAR
Foam inserts	No	No
Oil weight	350 cst	350 cst
Pistons	4x1.1mm	4x1.1mm
Rebound	0 %	0 %
Springs	2.5-2.8C	2.6C
Stroke	8.5 mm	8.5 mm

Shock oil brand: Hudy

DRIVETRAIN

Belts	Low-friction
Diff fluid brand	HUDY
DIFFS	
Front type	Solid axle
Rear fluid	10,000 cst
Drive ratio - final	4.63
Drive ratio - internal	1.9
Driveshafts - front	58mm BB ECS
Driveshafts - rear	54mm BB CVD
Gear pitch	64
Pinion	41 teeth
Spur	100 teeth

BODY & CHASSIS

Battery position	Centre
Body	Wolfrine 0.5
BODY MOUNTS	
Front height	26.5 mm
Front post-to-window distance	64.5 mm
Rear bumper height	59 mm
Rear type	Horizontal
Body stop height	18.5 mm
Bumper	Light and strong
FLEX	
Chassis	Aluminum
Chassis T-brace	No
Motor mount screws	3, 4, 5
Servo mount	Forward
Steering bridge brace	No
Top deck	Front '23 with bridge, Rear '23
Top deck screws	2, 3
Motor shims	2 mm
Rear wing	Twister
Rear wing side dam	Yes
Screws & turnbuckles	Titanium
Weight balance - F/R	51 / 49
Weight: total	1316 g

ELECTRONICS

Battery brand	**LRP**
Battery capacity	**6100 mAh**
Battery model	**Graphene 4**
ESC brand	**Hobbywing**
ESC model	**XERUN XR10 PRO G2S ELITE**
Motor brand	**Trinity**
Motor timing	**50 degrees**
Motor wind	**25.5 turns**
Radio brand	**Sanwa/Airtronics**
Radio EPA brake	**80 %**
Radio EPA throttle	**100 %**
Radio model	**M17**
Receiver brand	**Sanwa/Airtronics**
Receiver model	**RX-492**
Steering servo brand	**Power HD**
Steering servo model	**S15-X**

NOTES Cycle