Tamiya TRF420X

Setup: TRF420X MRCP Series 17,5 Parndorf 2024 · Rainer Konrath · May 15, 2024

so dialed
Open/save in RC Setup App →

Scan to open in the app

EVENT

Event	Mrcp Series 17,5T
Class	17.5 Stock

TRACK

Track	Mrc Wr.Neustadt
Type	Outdoor asphalt
Grip / moisture	Medium / Dry
Surface / layout	Medium / Open/Medium
Air temp	25°C (77°F)
Track temp	27.5°C (82°F)

FRONT SUSPENSION

ACKERMANN

Inner steering link shims	1 mm
Steering arm	Kit
Steering post	8.0mm
Anti-roll bar	1.3mm White
Bump steer: outer steering link shims	3 mm
Camber	-1.5 degrees

CAMBER LINKS

Inner link shims	2 mm
Inner mount shims	1 mm
Outer link shims	0.7 mm
Differential height	Low
Droop	5,6 mm
FF mount	Aluminum E
FF mount inserts	0.5 out
FF mount shims	0 mm
FR mount	Aluminum E
FR mount inserts	0.5 out
FR mount shims	0 mm
Hub carriers	Kit
Ride height	5,2 mm

SHOCKS

Arm mount location	B - Middle
Arm mount shims	2 mm
Tower mount location	2 - Middle
Tower mount shims	1.5 mm
Steering blocks	Kit
Steering stop angle	22° degrees
Toe	-1 degrees

TRACK

Wheel hexes	4mm
Wheel shims	0 mm
Wheelbase: arm spacers - F/R	0 / 1.5 mm

ELECTRONICS

Battery brand	Intellect Pioneering
Battery capacity	6000 mAh
Battery model	CC2S6000PT2
ESC brand	LRP
ESC model	FlowX
ESC settings	1-0 2-1 3-0 4-5 5-5 6-0 7-0 10-0
Motor brand	Trinity
Motor model	Slot Machine
Motor timing	47 degrees
Motor wind	17.5 turns

REAR SUSPENSION

Anti-roll bar	1.2mm
Camber	-2 degrees

CAMBER LINKS

Inner link shims	2 mm
Inner mount shims	1 mm
Outer link shims	1.5 mm
Differential height	Low
Droop	4,8 mm
RF mount	Aluminum A
RF mount inserts	0.5 in
RF mount shims	0 mm
Ride height	5,4 mm
RR mount	Aluminum E
RR mount inserts	0.5 in
RR mount shims	0 mm

SHOCKS

Arm mount location	B - MIddle
Arm mount shims	0.5 mm
Tower mount location	2 - Middle
Tower mount shims	1 mm

TRACK

Wheel hexes	4mm
Wheel shims	0 mm
Uprights	Kit
Wheelbase: arm spacers - F/R	0.5 / 1 mm

TIRES

	FRONT	REAR
Tire additive area	In, Mid-in, Mid-out, Out	In, Mid-in, Mid-out, Out
Tire brand / type	Tpro TP440236WH	Tpro TP440236WH
Tire compound	36	36

Tire additive	MR33 V3
Tire prep	20min 65°

SHOCKS

	FRONT	REAR
Oil weight	400 cst	450 cst
Pistons	4-hole	4-hole
Rebound	0 %	0 %
Springs	Axon blue/red	Axon white/green
Stroke	8.5 mm	8.5 mm

Shock oil brand	MuchMore

DIFFERENTIALS

	FRONT	REAR
Diff type	Solid axle	Gear
Diff fluid	–	5,000 cst
Diff mass	–	1.3 g

DRIVETRAIN

Drive ratio - internal	1.85
Driveshafts - front	Double-joint CVD
Driveshafts - rear	CVD
Pinion	45 teeth
Spur	100

BODY & CHASSIS

Body	Zooracing Anti
Body position	+1 forward
Bumper	Kit

FLEX

Chassis	Carbon fiber
Mount mount screws	1 - Front, 3, 4
Upper deck	420X
Upper deck screws	3
Rear wing	Standard
Weights	Only 20g Center weight
Wheelbase	Kit mm

NOTES Bearing Screw un the Upperdeck, and in the middle of the Topdeck i used a Hollowscrew