Custom Works Outlaw 5

Setup: Auburn RC · The Cop (SKRC) · Aug 31, 2025

so dialed
Open/save in RC Setup App →

Scan to open in the app

EVENT	
Event	Club

TRACK	
Track	Auburn
Type	Outdoor blue groove
Grip / moisture	High / Dry
Surface / layout	Smooth / Medium
Air temp	100°F (38°C)
Track temp	135°F (57°C)

FRONT SUSPENSION

Ackermann: outer steering link hole	L Front · R Rear
Camber	L +2 · R -3 degrees
CAMBER LINK	
Inner location	Outside mid-top
Outer location	L Kingpin · R Kinpin
Caster	L 0 · R -5 degrees
Kick-up	20 degrees
Max chassis height	L 11 · R 12.5 mm
Ride height	L 17 · R 19 mm
SHOCKS	
Arm mounts	Middle
Tower mounts	Center Mid-top
Toe	0 degrees
Trail: steering blocks	Std
Wheelbase: hub carrier shims	Middle

BODY & CHASSIS

Front wing	Large
Ride height measured from chassis	Bottom
Top wing height	High
Top wing location	C4
Weight: corners	LF: RF: LR: RR:

REAR SUSPENSION

Anti-squat	0 degrees
Arms	Short (v2)
Axle height: hub pin location	Upper
Camber	L +1 · R -1 degrees
CAMBER LINK	
Inner location	Inside
Outer location	Out
Outer shims	1
Max chassis height	13/14 mm
Ride height	L 18 · R 19 mm
SHOCKS	
Arm mounts	In
Tower mounts	Center-in/Middle / Center-in/Middle
Suspension mount	Wide (v2)
Toe	L -8 · R +8 degrees
Track: wheel hexes	5.5 / 5.5 mm
WHEELBASE	
Arm shims	0 mm
Hub shims	L 4 · R 2 mm
Suspension mount	Long

ELECTRONICS

Battery brand	Gens Ace
Battery capacity	6000 mAh
Battery model	2.0

SHOCKS

	FRONT	REAR
Bodies	L	L
Cups	Std	Std
Oil weight	25	30
Pistons	M	M
Pre-load	0.20	0.30
Shaft length	L	L
Shock length	3.18	3.18
Springs	L Grn · R Red	L Red · R Purple

DRIVETRAIN

Clutch	None
Differential fluid	2,000 cst
Differential fluid brand	AE
Differential type	Gear
Drive ratio - internal	2.61
Pinion	34 teeth
Spur	81 teeth

TIRES

	FRONT	REAR
Tire brand / type	Bald Eagle	Bald Eagle
Tire compound	MX	MX
Tire insert	Stock	Stock
Wheel brand / type	JConcepts	JConcepts
Tire prep	TDK	