Serpent SRX8E PRO

Setup: Park Lane Hobbies · Ken Grace (Team Associated) · Feb 13, 2026

so dialed
Open/save in RC Setup App →

Scan to open in the app

TRACK

Track	Park Lane Hobbies
Type	Outdoor clay
Grip / moisture	Low/Medium / Dry/Dusty
Surface / layout	Medium / Tight

FRONT SUSPENSION

Anti-roll bar	2.3mm
Arm inserts - bottom	None
Arm inserts - top	None
Camber	-1 degrees
CAMBER LINK	
Inner stud location	5 - Outside middle
Outer stud location	A - Inside
Hub carriers	17 degree
Kick-up: FF mount inserts	10 degrees - middle
Ride height	25 mm
SHOCKS	
Arm mounting hole	B - Outside
Tower mounting hole	3 - Middle-out
Steering arm	Type 2
Steering block	Kit
Steering link: outer stud spacers	0 mm
Steering stop	0 mm
Toe	-1 degrees
Tower	Aluminum
Track: wheel hexes	+1mm light

BODY & CHASSIS

Battery layout	Stick / 4S Brick
Body	SRXE
Chassis	Aluminum
Rear wing	Jconcepts Razor
Rear wing angle	4 degrees
Rear wing gurney strip	No
Rear wing mount	SRX8 v2
Screws & turnbuckles	Lunsford Titanium Turnbuckles

REAR SUSPENSION

Anti-roll bar	2.5mm
Anti-squat: RF block inserts	2.0 degrees - middle
Arm inserts - bottom	None
Arm inserts - top	None
Camber	-1 degrees
CAMBER LINK	
Inner stud location	5 - Outside bottom
Outer stud location	D - Outside
Hub inserts (Hub #600986)	Outside mid-top
Hubs	Aluminum v2 w Inserts
Ride height	27 mm
SHOCKS	
Arm mounting hole	C - Outside
Tower mounting hole	4 - Middle-out
Toe in: RR block inserts	3.0 degrees
Tower	Aluminum
Track width: hub pin position	Narrow (pin out)
Track: wheel hexes	+0mm light
Wheelbase: hub spacers	+2.5 mm

TIRES

	FRONT	REAR
Tire brand / type	AKA Impact	–
Tire compound	SSLW	–
Tire insert	Closed-cell	–
Wheel brand / type	AKA	–

SHOCKS

	FRONT	REAR
Oil weight	600 cst	550 cst
Pistons	VRP XV4 20-Hole	VRP XV4 20-Hole
Rebound	0 mm	0 mm
Shafts	Front	Rear
Shock length	108 mm	127 mm
Shock type	Emulsion	Emulsion
Springs	5.3 lb Purple	3.8 lb Purple
Stroke	36.5 mm	44 mm
Shock oil brand	PT RC	

DIFFERENTIALS

	FRONT	REAR
Diff fluid	5,000 cst	3,000 cst
Diff mass	43.5 g	43.5 g
Diff type	HTD	HTD
Center diff fluid	5,000 cst	
Center diff mass	44.0 g	
Center diff type	HTD	
Diff fluid brand	PT RC	

DRIVETRAIN

Driveshafts - center rear	Kit
Driveshafts - front	98mm
Driveshafts - rear	98mm
Pinion	16 teeth
Spur	44 teeth

ELECTRONICS

Battery brand	Factory Xtreme
Battery capacity	6400 mAh
Battery model	4S LiHV
ESC brand	Hobbywing
ESC model	XR8 Pro G3
Motor brand	Hobbywing
Motor Kv constant	1900 Kv
Motor model	Xerun 4268
Radio brand	Sanwa/Airtronics
Radio model	M17
Receiver brand	Sanwa/Airtronics
Receiver model	RX-493i
Steering servo brand	Sanwa/Airtronics
Steering servo model	PGS-XR II