Schumacher Mi9

Setup: Winters series M2 · Jost Julien (Schumacher) · Nov 25, 2024

so dialed
Open/save in RC Setup App →

Scan to open in the app

EVENT

Event	Winters series manche 2

TRACK

Track	Longwy
Type	Indoor carpet
Grip / moisture	Medium / Dry/Dry
Surface / layout	Medium/Bumpy / Medium

FRONT SUSPENSION

ACKERMANN	
Inner steering link shims	0 mm
Outer steering link location	2 - Out
Anti-roll bar	1.3 mm
Axle height: hub shims	0 mm
Bump steer: outer steering link shims	1 mm
Camber	-2 degrees
Caster	4 degrees
Droop	23.6 mm
FF arm mount shims	0.5 mm
FR arm mount shims	1 mm
Hub carriers	Plastic
Ride height	5.2 mm
Servo horn height	17 mm
Servo horn type	Horn
Shocks: tower mounts	2 - Out
Spool height	High, High transmission housing
Steering travel - in/out	26/ 0 degrees
Toe	-1.5 degrees
TRACK	
Axle shims	0 mm
Wheel hexes	Kit
Upper link mounts	0 dot
UPPER LINKS	
Inner shims	2 mm
Outer shims	1 mm

ELECTRONICS

Battery brand	MARKA
Battery C rating	140 C
Battery capacity	6600 mAh
ESC brand	Hobbywing
ESC model	G3x
Motor brand	Hobbywing
Motor model	17.5t G4r
Motor timing	38 degrees

REAR SUSPENSION

Anti-roll bar	1.2 mm
Axle height: hub shims	0.5 mm
Camber	-2 degrees
Caster	2.5 degrees
Differential height	High, High transmission housing
Droop	22.6 mm
Hub carriers	Plastic
RF arm mount shims	1 mm
Ride height	5.4 mm
RR arm mount shims	1 mm
Shocks: tower mounts	1 - In
Toe - static	2 degrees
TOE LINK	
Inner shims	3 mm
Outer shims	2.5 mm
TRACK	
Axle shims	0 mm
Wheel hexes	Kit
Upper link mounts	0 dot
UPPER LINKS	
Inner shims	2 mm
Outer shims	1 mm

TIRES

	FRONT	REAR
Tire additive time	30 min	30 min
Tire brand / type	Rush 28	Rush 28
Tire additive	Phub blanc	
Tire glue diameter	Front 60 mm	

ESC SETTINGS

BOOST	
Activation	Auto
Timing	30 degrees
Brake: Frequency	4 kHz
Throttle: Frequency	8 kHz
TURBO	
Delay	0.1 seconds
Timing	30 degrees

SHOCKS

	FRONT	REAR
Limiters: ext	0 mm	0 mm
Oil weight	300 cst	300 cst
Pistons	4 x 1mm	4 x 1mm
Rebound	0 mm	0 mm
Springs	2.7 xray	2.7 xray
Stroke	8 mm	8 mm
Shock bodies	Standard	
Shock oil brand	MARKA	

DRIVETRAIN

DIFFS	
Rear fluid	6,000 cst
Rear fluid mass	1.6 g
Drive ratio - final	5.03
Drive ratio - internal	1.818
Gear pitch	64
Pinion	39 teeth
Spur	108 teeth

BODY & CHASSIS

Body	Xtreme twister
BODY POSTS	
Front hangers	2 dot
Front pin hole	5
Rear hangers	1 dot
Rear pin hole	9
Body stop height	6 mm
FLEX	
Chassis	Aluminum
Chassis brace	None
Motor mount screws	3, 4
Upper deck	S2 Front 1.6mm, S2 Rear 1.6mm
Upper deck dowels	2-piece front: rear, 2-piece rear: front
Rear wing	Xtreme médium precut
Rear wing side dams	Yes
Weight balance - F/R	50 / 50 %
Weight: total	1305 g