Xpress EXECUTE XM1S

Setup: My Base Setup · Riley Johnson (SpeedRC) · Dec 27, 2024

so dialed
Open/save in RC Setup App →

Scan to open in the app

EVENT	
Event	Friday Night Race

TRACK	
Track	Kettering
Type	Indoor carpet
Grip / moisture	Medium / Dry
Surface / layout	Smooth / Tight

RESULTS	
Race type	Qualifier
Race number	1

FRONT SUSPENSION

ACKERMANN	
Inner steering link spacers	0 mm
Outer steering stud location	1 - Outside
Anti-roll bar	1.3 mm
Arms	Medium
Bumpsteer: outer steering stud spacers	0 mm
CAMBER LINK	
Inner stud spacers	0 mm
Outer stud spacers	0 mm
Differential height	Low
FF mount	Composite
FF mount inserts	0 center
FF mount spacers	0 mm
FR mount	Split composite
FR mount inserts	0 center
FR mount spacers	0 mm
Hub carriers	Composite 4-degree
SHOCKS	
Arm mount spacers	1.0 mm
Arm mounting hole	B - Middle
Tower mount spacers	1.0 mm
Tower mounting hole	2 - Middle
Steering block plates	Medium
Steering blocks	Medium
Tower	FRP
Track: wheel hexes	Composite
Wheelbase: arm spacers - F/R	3 / 2 mm

REAR SUSPENSION

Anti-roll bar	1.3 mm
Arms	Medium
CAMBER LINK	
Inner stud spacers	0 mm
Outer stud location	A - Inside
Outer stud spacers	2.0 mm
Differential height	Low
RF mount	Split composite
RF mount inserts	0 center
RF mount spacers	0 mm
RR mount	Composite
RR mount inserts	0 center
RR mount spacers	0 mm
SHOCKS	
Arm mount spacers	1.0 mm
Arm mounting hole	D - Mid-out
Tower mount spacers	1.0 mm
Tower mounting hole	2 - Middle
Tower	FRP
Track: wheel hexes	Composite
Uprights	Medium
Wheelbase: arm spacers - F/R	0 / 4 mm

SHOCKS

	FRONT	REAR
Bodies	Composite	Composite
Oil weight	450 cst	450 cst
Pistons	2-hole	2-hole
Springs	1.4 Blue	1.4 Blue
Stroke	11 mm	11 mm

DIFFERENTIALS

	FRONT	REAR
Diff fluid	–	5,000 cst
Diff fluid mass	–	1.3 g

Front diff type	Spool

DRIVETRAIN

Drive ratio - internal	1.9
Gear pitch	64
Spur	96 teeth

BODY & CHASSIS

FLEX	
Chassis	FRP
Upper deck	FRP

TIRES

	FRONT	REAR
Tire brand / type	Valanta	Valanta
Tire compound	28	28
Tire insert	Pink	Pink
Wheel brand / type	Plastic	Plastic
Additive area	–	Full tire

Tire glue diameter - F/R	- / - mm