

Setup: My Base Setup

Name: Wesley Knapp Date: October 10, 2025 Event: Ambient Temp: 24C/75F

Track: INDOOR ☐ OUTDOOR ☒ Size: SMALL ☐ MEDIUM ☒ LARGE ☐ Traction: LOW ☐ MEDIUM ☒ HIGH ☐

Surface: SMOOTH ☐ BUMPY ☒ RUTTED ☐ Type: LOOSE / LOAMY ☒ HARD PACKED ☐ BLUE GROOVE ☐ CLAY ☐ ASTRO ☐

Ackerman/Bumpsteer/Arm Plate/Spindle Height/Servo Saver Condition: DUSTY ☒ DRY ☐ WET ☐ MUDDY ☐



WASHERS: 4




WASHERS: 0
PLATE: **ABCEFGH**



SPINDLE PART#
TKR9141 (+1,0)
TKR9141B (-1, -2)



FULL TURNS FROM FULLY TIGHT: 1



(FRONT) (REAR) SWAY BAR BUSHINGS

Front End:

TOWER: 2.2

UNI/CVD: U - TKR9487, C - TKR9472

STANDOFF: 0mm, +2mm, +4mm

OFFSET: 2mm, 3mm, 4mm

"A" Block: TKR9461 (0mm), TKR9461B (-1mm)

Suspension:

RIDE HEIGHT:	34	CAMBER:	-2
CASTER BLOCK:	18 deg	SWEEP:	0
KICK UP:	10	TOE:	-2
SWAY BAR:	2.2	SHOCK LENGTH:	
UP TRAVEL LIMITERS:	0	DROOP:	0
OIL:	500 cst	BRAND:	Tekno
PISTON:	MIP 6x1.3mm HF	SPRING:	5.17lb Green
REBOUND:	0	BUILD:	Emulsion

"B" Block: TKR9462 (0mm), TKR9462B (-1mm)

Differentials:

OPTION	FRONT	CENTER	REAR
Diff Oil 	7,000	10,000	5,000
(TKR5144B) 	☒	☒	☒
(TKR5144) 	☐	☐	☐
(TKR5145B) 	☒	☒	☒
(TKR9145) 	☐	☐	☐
Standard (TKR9114-TKR9112) 	☒	☒	☒
Lightened (TKR5114XB-TKR5112x) 	☐	☐	☐
(TKR9150) 	☐	☐	☐
(TKR9150B) 	☒	☒	☒
(TKR9115C) 	☐	☐	☐
(TKR9115B) 	☒	☒	☒
(TKR9149) 	☒	☒	☒
(TKR9149A) 	☐	☐	☐

Rear End:

TOWER: 2.2

UNI/CVD: U - TKR9487, U - TKR9687, C - TKR9472

STANDOFF: 0mm, +2mm, +4mm

REAR HUB: 

OFFSET: 2mm, 3mm, 4mm

"C" Block: Screw (TKR1324)

Suspension:

RIDE HEIGHT:	38	CAMBER:	-2
ANTI-SQUAT:	3	TOE:	2
SWAY BAR:	2.4	SHOCK LENGTH:	
UP TRAVEL LIMITERS:	+2 Shock Eyelets	DROOP:	-8
OIL:	400 cst	BRAND:	
PISTON:	MIP 6x1.4 HF	SPRING:	5.17lb Green
REBOUND:	0	BUILD:	Emulsion

Chassis Braces:

MIDDLE: ☐ REAR: ☒

Tires / Wheels:

BRAND / TREAD:	
COMPOUND:	
INSERT:	
WHEEL:	
NOTES:	

Body / Wing:

BODY MAKE:	Kit
WING MAKE:	Kit
WING MOUNT POSITION:	
0mm: ☐ +7mm: ☐ +12mm: ☒	
NOTES:	

Bulkheads:

FRONT: TKR9416 (0mm) ☐ TKR9416B (-2mm) ☒

REAR: TKR9416 (0mm) ☐ TKR9416B (-2mm) ☒

Drivetrain:

PINION / SPUR: 16 / 44 (teeth)

Equipment:

ESC: MOTOR:

BATTERY: SERVO:

Notes:

Open in So Dialed App

Wheelbase:

REAR FRONT

F/R: 2 / 3

(Shims) Thick - 2mm Thin - 1mm