ARRMA Limitless

Setup: Limitless V2 · K Tran · Apr 29, 2026

so dialed
Open/save in RC Setup App →

Scan to open in the app

EVENT

Event	Course Race

TRACK

Track	Course Race
Type	Outdoor asphalt
Grip / moisture	Medium/Medium / Dry/Dry
Surface / layout	Smooth/Medium/Smooth/Medium / Medium
Air temp	45°F (7°C)
Track temp	45°F (7°C)

FRONT SUSPENSION

Anti-roll bar	2.6mm
Bump steer: outer steering stud shims	0 mm
Camber	-1 degrees
Caster: upper arm shims - F/R	0 / 3 mm
Droop	90 mm
FF suspension mount	Aluminum
FR suspension mount	Aluminum
Lower arms	Medium
Ride height	19 mm
Shocks: tower mounting hole	1 - Inside
Toe	-2 degrees
Tower	Aluminum
Track: wheel hexes	14.6mm
Upper arms	Medium

TIRES

	FRONT	REAR
Tire brand / type	GRP GTY03	GRP GTY03
Tire compound	XB2 Extra Soft	XB2 Extra Soft
Wheel brand / type	GRP	GRP

ESC SETTINGS

Brake: Drag	10 %
THROTTLE	
Neutral range	8 %
Strength	65

REAR SUSPENSION

Anti-roll bar	2.7mm
Arms	Medium
Camber	-1 degrees
CAMBER LINK	
Inner stud location	1 - Inside bottom
Outer stud location	C - Outside bottom
Droop	88 mm
RF suspension mount	Composite
Ride height	19 mm
RR suspension mount	Composite
Shocks: tower mounting hole	2 - Middle
Tower	Aluminum
Track: wheel hexes	16.5mm
Wheelbase: hub shims - F/R	0/4 mm

BODY & CHASSIS

	FRONT	REAR
Wing trim	15mm	15mm

Battery position	Saddle
Body	GX BLX
Diffusers	Front, Rear
Rear wing	GS BLX

ELECTRONICS

Battery brand	CNHL
Battery C rating	120 C
Battery capacity	6600 mAh
Battery model	3S
ESC brand	Hobbywing
ESC model	Max6 G2
Motor brand	Hobbywing
Motor Kv constant	1650 Kv
Motor model	Max6 G2 4990
Radio brand	Futaba
Radio model	T4PM
Receiver brand	Futaba
Steering servo brand	Savox

SHOCKS

	FRONT	REAR
Oil weight	1300	1300
Pistons	8x1.2	8x1.2
Springs	35mm 6.6N	40mm 6.6N

NOTES 1/26' - NEW shock fluids

DIFFERENTIALS

	FRONT	REAR
Diff fluid	100,000 cst	30,000 cst

Center diff fluid	Spool
Center diff type	Spool
Diff fluid brand	PT Racing

NOTES 1/26' - fresh front/rear fluids

DRIVETRAIN

Drive ratio - final	4.17
Drive ratio - internal	2.8
Driveshaft - center front	102mm dogbone
Driveshaft - center rear	168mm dogbone
Driveshafts - front	94mm CVD
Driveshafts - rear	116 Dogbone (AR310472)
Pinion	24 teeth
Spur	39 teeth

NOTES 1/26' - NEW diff fluids

*24/39 = 94 MPH