Schumacher

CATPB

Driver: Schumacher **Date:** September 11, 2025 **Event/Track:** Champs

Qualify: **Final:** **Best Lap:**

TRACK TYPE

Grip Level	High ☐ Medium ● Low ☐
Type	Tight ☐ Open ☐ Mixed ●
Condition	Flat ☐ Bumpy ☐ Mixed ●
Surface	Clay ☐ Long Astro ● Carpet ☐ Grass ☐ Short Astro ☐ Mixed ☐
Weather	

TYRES

	FRONT	REAR
Tyres		
Wheels		
Inserts		

Notes:

Notes:

Setup: Mod Astro Kit Setup

Open in So Dialed App

FRONT SUSPENSION

KEY: **P** = Plastic, **A** = Alloy, **B** = Brass, **CF** = Carbon Fibre, **S2** = Schumacher Composite, **M** = Medium, **S** = Stiff, **Sh** = Short, **H** = High, **L** = Low, **F** = Front, **R** = Rear, **Y** = Yes, **N** = No

More: sodialed.com/setups

Ride Height	15 mm
Toe	-1 deg In ☐ Out ☐
Camber at Ride Height	-1.5 deg
ARB	N/A ☐ 1.0 ☐ 1.1 ☐ 1.2 ☐ 1.4 ☐ 1.6 ● 1.8 ☐ 1.9 ☐ 2.0 ☐ 2.1 ☐
Driveshaft Type	CVD ☐ Roche ☐ U/J ●
Steering Arm	Kit ● 1 Dot ☐ 2 Dot ☐ 3 Dot ☐

Washers 2 mm

CTR P ☐ A ☐

Washers 0 mm

Shock Mount S2 ● CF ☐

Shim 2 mm

Front Wing Yes ☐

Hub Carrier P ● A ☐

6° ☐ 8° ☐ 10° ●

P ● A ☐ Yoke

2 mm Washers

'A' Mount

'B' Mount

2.50mm High ☐ | 1.25mm High ☐ | 0.00mm Mid ● | 1.25mm Low ☐ | 2.50mm Low ☐

Hex

-2.0 ☐ -1.50 ☐ -1.00 ●

-0.75 ☐ 0 ☐ 0.75 ☐

M ● CF ☐ Wishbone

F mm

R 3 mm

WheelBase

REAR SUSPENSION

KEY: **P** = Plastic, **A** = Alloy, **B** = Brass, **CF** = Carbon Fibre, **S2** = Schumacher Composite, **M** = Medium, **S** = Stiff, **Sh** = Short, **H** = High, **L** = Low, **F** = Front, **R** = Rear, **Y** = Yes, **N** = No

Ride Height	15 mm
Camber at Ride Height	-2 deg
ARB	N/A ☐ 1.0 ☐ 1.1 ☐ 1.2 ☐ 1.4 ☐ 1.6 ☐ 1.8 ☐ 1.9 ☐ 2.0 ● 2.1 ☐
Wing Gurney Height	5 mm
Driveshaft Type	CVD ☐ U/J ●
High Roll Centre Straps	Y ☐ N ☐

Hub Carrier P ● A ☐

Hub/Axle Height

3 2 1 0 -1 -2 -3

High Low

Shock Mount S2 ● CF ☐

Eccentric P ☐ A ☐

Hex

-2.00 ☐ -1.50 ● -1.00 ☐

-0.75 ☐ 0 ☐ 0.75 ☐

2 mm Washers

Wheelbase

0 ☐ +2 ● +4 ☐ +6 ☐

H ☐ L ● Strap Options H ☐ L ●

'C' Mount

Slipper

'D' Mount

2.50mm High ☐ | 1.25mm High ☐ | 0.00mm Mid ● | 1.25mm Low ☐ | 2.50mm Low ☐

M ● CF ☐ Flipped ☐ Wishbone

TRANSMISSION

Lock Out	Y ☐ N ☐
Slipper Plates	2 ☐ 3 ●

Differential Oil

Front (cSt)	Centre (cSt)	Rear (cSt)
12,000	N/A	12,000
Gears 2 ☐ 4 ●	Gears 2 ☐ 4 ☐	Gears 2 ☐ 4 ●

Centre Transmission

F.A.B	Lock Out	Gear Diff
Y ● N ☐	Y ☐ N ☐	Y ☐ N ☐

Notes:

EQUIPMENT

E.S.C.	
Servo	
RX	
LiPo	
Bodyshell	Kit
Wing	Aerox Trident LD3
Motor	
Timing	deg
Pinion	T
Spur	83 T

CHASSIS

LiPo Position	1 ☐ 2 ● 3 ☐
Running Weight	g
Front Deck	Y ● N ☐
Rear Deck	Y ● N ☐
Chassis Length	S ☐ L ●

WEIGHTS

Notes:

SHOCKS

KEY: **i** = Internal, **e** = External, **V** = Vented, **S** = Sealed, **A** = Aeration

	FRONT	REAR
Cap	V ☐ S ☐ A ●	V ☐ S ☐ A ●
Kashima	Y ☐ N ●	Y ☐ N ●
Oil	550 cst	400 cst
Piston	2 x 1.6mm tapered	2 x 1.8mm tapered
Spring	3.7lb Blue	2.2lb Green
Limiters (i)	0 mm	0 mm
Stroke	22 mm	28.5 mm
Limiters (e)	0 mm	o-ring mm
Stand Off	mm	mm