Traxxas Slash 2WD

Setup: WaldoRC Carpet · David P · Nov 2, 2025

so dialed
Open/save in RC Setup App →

Scan to open in the app

TRACK

Track	Waldo Indoor
Type	Indoor carpet
Grip / moisture	High / Dry
Surface / layout	Smooth / Tight
Air temp	75°F (24°C)

FRONT SUSPENSION

Anti-roll bar	None
Arms	Kit
Camber	-3 degrees
Hub carriers	Kit 30 degree
Shocks: arm mounting hole	B - Outside
Steering bellcrank	Aluminum
Steering blocks	Kit
STEERING LINK	
Inner stud spacers	0 mm
Outer stud spacers	0 mm
Toe	-0.5 degrees
Tower	RPM
Track: wheel hexes	12mm

TIRES

	FRONT	REAR
Tire brand / type	Traxxas SCT	Traxxas SCT
Tire compound	SPEC	S1

NOTES Fronts taped 15mm

REAR SUSPENSION

Anti-roll bar	None
Arms	Kit
Camber	-3 degrees
Hubs	Aluminum
ROLL CENTER	
Hub pin location	Lower
Inner camber link location	Lower
Shocks: arm mounting hole	C - Middle
Tower	RPM
Track: wheel hexes	12mm

DRIVETRAIN

Differential fluid	1,000,000 cst
Differential type	Gear
Drive ratio - internal	2.72
Drive type	Slipper
Driveshafts	Heavy duty
Pinion	21 teeth
Slipper clutch pads	Kit
Slipper tightness	Full tight
Spur	90 teeth

SHOCKS

	FRONT	REAR
Bodies	Ultra long	Ultra XX-long
Limiters - internal/external	0 / 0 mm	0 / 0 mm
Oil weight	45 wt TA	40 wt Losi
Pistons	2-hole	2-hole
Shafts	Titanium Nitride Long	Titanium Nitride XX-Long
Springs	Progressive Pink	Progressive Pink
Shock oil brand	Traxxas	

BODY & CHASSIS

Battery position	Front
Body	TRX Slash
Chassis	Low CG
Rear wing	Kit
Rear wing height	High
Weight balance - F/R	- / -

ELECTRONICS

Battery brand	Gens Ace
Battery capacity	6000 mAh
Battery model	Redline
ESC brand	Traxxas
ESC model	XL-5
Motor brand	Traxxas
Motor model	Titan 12T
Motor wind	12 turns
Radio brand	Flysky
Receiver brand	Flysky
Servo brand	Savox