1RC Late Model 1/18

Setup: 2025-11-22 Battle in the Warehouse · George Mari · Nov 24, 2025

so dialed
Open/save in RC Setup App →

Scan to open in the app

EVENT

Event	2025-11-22 Battle in the Warehouse
Class	Dirt Late Model

TRACK

Track	2025 RC Warehose
Type	Indoor rcp foam
Grip / moisture	High/Medium / Dry
Surface / layout	Smooth / Medium
Air temp	60°F (16°C)
Track temp	60°F (16°C)

RESULTS

Race type	Main
Race number	A
Finish	3rd
Best lap	2.87 s
Average lap	3.531 s

FRONT SUSPENSION

LF caster	**+2 degrees**
LF ride height	**8 mm**
RF caster	**2**
RF ride height	**7 mm**
Servo arm hole	**Upper**
Servo arm type	**Servo saver**

NOTES Using coil-over front suspension springs.

TIRES

LF tire compound	**Soft**
LR tire compound	**Soft**
RF tire compound	**Soft**
RR tire compound	**Soft**

NOTES Glue pattern on RF tire is 12 triangles extending from middle of tire to edge. One block with no glue between triangle on the edge of the tire.

ESC SETTINGS

BRAKE

Drag force	**20 %**
Initial force	**0 %**
Max force	**50 %**
Low voltage cut-off	**Disabled**
Max reverse force	**50 %**
Neutral range	**9 %**
Overheat warning	**Enabled**
Running mode	**FWD / Brake**
Start mode / punch level	**9**
Timing	**26.25 degrees**

REAR SUSPENSION

LR hex offset	**0 mm**
LR ride height	**8 mm**
RR hex offset	**1 mm**
RR ride height	**7.5 mm**

NOTES LR adjustable tie rod 5 turns shorter than normal. LR ball stud for shock is backed out 3 or 4 turns to compensate. Make sure LR shock moves smoothly.

BODY & CHASSIS

Motor heatsink	**Yes**

ELECTRONICS

Battery brand/model	**Turnigy**
Battery C rating	**90 C**
Battery capacity	**300 mAh**
Battery cells	**2**
Battery type	**LiPo**
ESC	**1RC**
Motor brand/model	**1RC**
Motor Kv constant	**8,700 Kv**
Radio	**Flysky GT5**
Radio dual-rate	**50 %**
Radio EPA brake	**120 %**
Radio EPA throttle	**120 %**
Receiver	**Flysky GT2E**
Servo	**1RC**
Transponder ID	**3765**

NOTES Steering exponential 65 pct; Left trim 05

SHOCKS

LF body	**Plastic**
LF grease	**AE Greenn Slime**
LF o-ring	**Clear**
LF pre-load	**1 mm**
LF spring	**Short Medium**
LF stroke	**6.35 mm**
LR body	**Plastic**
LR grease	**AE Green Slime**
LR o-ring	**Clear**
LR pre-load	**1 mm**
LR spring	**Short Hard**
LR stroke	**6.35 mm**
RF body	**Plastic**
RF grease	**AE Green Slime**
RF o-ring	**Clear**
RF pre-load	**1 mm**
RF spring	**Short Hard**
RF stroke	**6.35 mm**
RR body	**Plastic**
RR grease	**AE Green Slime**
RR o-ring	**Clear**
RR pre-load	**2 mm**
RR spring	**Short Medium**
RR stroke	**6.35 mm**
Shock caps	**Drilled**
Shock oil brand	**Team Associated**