TLR 22X-T

Setup: PDX RC Raceway 12/18 · Robb Hunter · Dec 24, 2025

so dialed
Open/save in RC Setup App →

Scan to open in the app

EVENT

Event	Vision series 5

TRACK

Track	PDX RC Raceway
Type	Indoor carpet
Grip / moisture	High
Surface / layout	Smooth / Tight
Air temp	70°F (21°C)
Track temp	70°F (21°C)

FRONT SUSPENSION

Ackermann: steering arms	Narrow
Anti-roll bar	1.7 mm
Arms	Stiffezel
Axle height	2.7 mm
Bulkhead	Aluminum
BUMP STEER	
Inner steering link shims	0 mm
Outer steering link shims	0 mm
Steering arm shims	0 mm
Camber	-2 degrees
CAMBER LINKS	
Inner	Mid
Inner shims	0 mm
Outer	Mid
Outer shims	1 mm
Caster block inserts	+0 degrees
Kick-up plate	25 degrees
Ride height	15 mm
SHOCKS	
Arm mounts	Mid
Tower mounts	Out
Steering block	Narrow
Toe	0 degrees
Tower	-2
TRACK	
Axle shims	0 mm
Wheel hexes	6 mm

NOTES Aluminum steering rack secondary hole

REAR SUSPENSION

Arms	Stiffezel
Axle height	+4 mm
C mount	Kit
C mount inserts	1 out, .5 down
Camber	-1 degrees
CAMBER LINKS	
Inner	Front
Inner shims	1 mm
Outer	Front
Outer mount shims	0 mm
Outer shims	1 mm
D mount inserts	1 down and in
Differential height	+4 mm
Hubs	Aluminum VHA
Ride height	15 mm
SHOCKS	
Arm mounts	Out
Tower mounts	In
Tower	-4
Track: wheel hexes	6 mm
WHEELBASE	
Arm shims - F/R	2 / 0.5 mm
Hub shims - F/R	3 / 0 mm

NOTES Upside down shocks. Tower +2mm forward

BODY & CHASSIS

Body	Kit
Chassis	Kit
FLEX	
Chassis side guards	Stiffezel
Chassis waterfall brace	Stiffezel
Motor plate	Carbon

NOTES Battery one hole from forward

SHOCKS

	FRONT	REAR
Cup offset	High	Mid
Eyelets	+0 mm	+2 mm
Limiters - ext	2 mm	2 mm
Limiters - int	0 mm	0 mm
Oil weight	45 wt	40 wt
Piston thickness	2.5 mm	2.5 mm
Pistons	2 x 1.7mm	2 x 1.8mm
Shaft diameter	3.0 mm	3.0 mm
Springs	4.75lb Purple	2.37lb Blue
Stroke	21 mm	26.5 mm

Shock oil brand: Team Losi

NOTES Avid 9 dot front 4.75
Avid 5 dot rear 2.45
Aluminum shock caps
Vision Upside down rear shocks

DRIVETRAIN

Clutch pads	Kit
Diff fluid	200,000 cst
Diff fluid brand	Team Losi
Diff gear material	Steel
Diff gears	2
Diff type	Gear
Drive ratio - internal	2.6
Drive type	Slipper
Driveshaft pin position	Out
Driveshafts	X92
Pinion	26 teeth
Spur	78 teeth

TIRES

	FRONT	REAR
Tire brand / type	J Concepts Swagger	J Concepts Pin Down
Tire compound	Pink	Pink
Tire insert	Standard	Standard
Wheel brand / type	Proline	Proline

NOTES Front glued to first rib