Traxxas Slash 2WD

Setup: My Base Setup · Jake Foster · Apr 6, 2026

so dialed
Open/save in RC Setup App →

Scan to open in the app

EVENT

Event	Club race

TRACK

Track	The Rc Shack
Type	Indoor carpet
Grip / moisture	High / Dry
Surface / layout	Smooth / Tight
Air temp	65°F (18°C)
Track temp	45°F (7°C)

FRONT SUSPENSION

Arms	Heavy duty
Camber	-1.5 degrees
Hub carriers	Kit 30 degree
Shocks: arm mounting hole	B - Outside
Steering bellcrank	Aluminum
Steering blocks	Kit
STEERING LINK	
Inner stud spacers	0 mm
Outer stud spacers	0 mm
Toe	-1 degrees
Tower	Kit
Track: wheel hexes	12mm

TIRES

	FRONT	REAR
Tire brand / type	Traxxas Bf Goodrich	Traxxas spec
Wheel brand / type	Traxxas	Traxxas
Tire prep - F/R	None	

NOTES Taped outside edge of fronts

REAR SUSPENSION

Anti-roll bar	None
Arms	Heavy duty
Camber	-1.5 degrees
Hubs	Kit
ROLL CENTER	
Hub pin location	Lower
Inner camber link location	Upper
Shocks: arm mounting hole	D - Mid-out
Tower	Kit
Track: wheel hexes	12mm

BODY & CHASSIS

Battery position	Front
Body	TRX Slash
Chassis	High CG
Rear wing	Kit
Rear wing height	High
Weight balance - F/R	- / -

ELECTRONICS

Battery brand	Zeee
Battery C rating	50 C
Battery capacity	5200 mAh
ESC brand	Traxxas
ESC model	BL-2s
Motor brand	Traxxas
Motor Kv constant	3300 Kv
Motor model	Bl-2s
Motor wind	12 turns
Radio brand	Flysky
Radio model	Noble nb4
Receiver brand	Flysky
Servo brand	Savox
Servo model	1258tg

SHOCKS

	FRONT	REAR
Bodies	Ultra long	Ultra XX-long
Limiters - internal/external	3 mm	1 mm
Oil weight	45 wt	40 wt
Pistons	2-hole	2-hole
Shafts	Kit	Kit
Springs	Progressive Blue	Progressive Orange
Shock oil brand	Traxxas	

DRIVETRAIN

Differential fluid	30w shock oil cst
Differential type	Gear
Drive ratio - internal	2.72
Drive type	Slipper
Driveshafts	Stock 6852X
Pinion	23 teeth
Slipper clutch pads	Kit
Slipper tightness	Full tight
Spur	86 teeth