



EVENT	
Event	Hooning

TRACK	
Track	Enka Clocktower
Type	Outdoor asphalt
Grip / moisture	Medium / Dusty
Surface / layout	Medium / Medium
Air temp	85°F (29°C)
Track temp	115°F (46°C)

FRONT SUSPENSION	
Anti-roll bar	2.4mm
Bump steer: outer steering stud shims	0 mm
Camber	-1 degrees
Caster: upper arm shims - F/R	0 / 3 mm
FF suspension mount	Aluminum
FR suspension mount	Aluminum
Lower arms	Medium
Ride height	15 mm
Shocks: tower mounting hole	2 - Outside
Tower	Aluminum
Track: wheel hexes	13.6mm
Upper arms	Medium

TIRES		
Tire brand / type	FRONT	REAR
	dBoots Hoons 42/100 2.9	dBoots Hoons 42/100 2.9
Wheel brand / type	ARRMA Black Aero Dish	ARRMA Black Aero Dish

REAR SUSPENSION	
Anti-roll bar	2.7mm
Arms	Medium
Camber	-1 degrees
Camber link: outer stud location	C - Outside bottom
RF suspension mount	Composite
RR suspension mount	Composite
Shocks: tower mounting hole	3 - Outside
Tower	Aluminum
Track: wheel hexes	13.6mm
Wheelbase: hub shims - F/R	2 / 2 mm

BODY & CHASSIS		
Wing trim	FRONT	REAR
	1 line	1 line mm
Diffusers	Front, Rear	
Rear wing	GS BLX	

	SHOCKS	
	FRONT	REAR
Oil weight	3000	3000
Pistons	6x1.3mm	6x1.3mm
Springs	35mm 6.6N	40mm 6.6N

DIFFERENTIALS		
Diff fluid	FRONT	REAR
	10,000 cst	10,000 cst
Center diff type	Differential	

DRIVETRAIN	
Drive ratio - final	4.17
Drive ratio - internal	2.8
Driveshaft - center front	102mm dogbone
Driveshaft - center rear	168mm dogbone
Driveshafts - front	94mm CVD
Driveshafts - rear	91mm CVD
Pinion	21 teeth
Spur	46 teeth