XRAY XB8 '26

Setup: Skellefteå 260709 · Nicklas Lindgren · Jul 9, 2026

so dialed
Open/save in RC Setup App →

Scan to open in the app

EVENT	
Event	Träning

TRACK	
Track	Hammarängen Skellefteå
Type	Outdoor astroturf
Grip / moisture	High / Dry
Surface / layout	Medium / Medium
Air temp	22.5°C (73°F)
Track temp	40°C (104°F)

RESULTS	
Best lap	36.839 s
Laps / time	81 / 1:19:42.683

FRONT SUSPENSION

ACKERMANN	
Inner steering link location	Mid-front
Steering arms	Carbon 3-dot
Anti-roll bar	2.4 mm
BUMP STEER	
Inner steering link shims	0 mm
Outer steering link shims	0 mm
Camber	-3 degrees
CAMBER LINKS	
FF inserts	1 down and in
FR inserts	1 down and in
Caster: upper link shims	2 mm
Differential height	Mid
FF mount inserts	1 in
FR mount inserts	1 in
Lower arms	Med
PIVOT BALL SHIMS	
Lower	0 mm
Upper	1 mm
PIVOT BALLS	
Lower	Steel
Upper	Aluminum
Ride height	22 mm
Servo saver tightness	Medium
SHOCKS	
Arm mounts	Out
Tower mounts	Mid
Steering blocks	Hard
Toe out	+1 degrees
Trail	Center
Upper arms	Medium
Wheelbase: arm shims	0 mm

REAR SUSPENSION

Anti-roll bar	2.6 mm
Anti-roll bar arm mount	Out
Anti-squat	1 degrees
Arms	Hard
Camber	-2 degrees
CAMBER LINKS	
Inner	In / up
Outer	Out
Differential height	Low
Droop	-11 mm
RF mount inserts	1 down and in
Ride height	25 mm
RR mount inserts	1 down and in
SHOCKS	
Arm mounts	Out
Tower mounts	Mid-out
Toe	3 degrees
Track: wheel hexes	+1 mm
Upright pin location	Out
Upright plates	N/A
Uprights	Hard
WHEELBASE	
Arm shims	4 mm
Hub shims	2 mm

ENGINE

Engine brand	REDS
Engine model	721 PRO-X Factory Team
Fuel	16%
Glow plug	OS p3
Pipe / header	Reds 2143

NOTES Timmer 6.50 minuter

SHOCKS

	FRONT	REAR
Membranes	O-ring	O-ring
Oil weight	600 cst	550 cst
Pistons	8 x 1.2mm	8 x 1.3mm
Shock length	104,5 mm	121 mm
Shock type	Emulsion	Emulsion
Springs	69mm 0.8-0.83C 4-dot	82mm 0.68-0.7C 3-dot
Stroke	34 mm	41 mm
Shock oil brand	XRAY	

DIFFERENTIALS

	FRONT	REAR
Diff case	Kit	Kit
Diff crown gear	46 teeth	46 teeth
Diff fluid	10,000 cst	3,000 cst
Diff gears	4	4
Diff mass	41.90 g	41.90 g
Diff pinion gear	13 teeth	13 teeth
Center diff case	v2	
Center diff fluid	7,000 cst	
Center diff mass	42.78 g	

DRIVETRAIN

Clutch shoes	2st aluminium medium, 2st grafit
Clutch springs	2st grå och 2st guld
Drive ratio - internal	3.539
Driveshafts - front	94mm CVD
Driveshafts - rear	93mm CVD
Pinion	14 teeth
Spur	46 teeth

NOTES Gråa fjädrar på alu skorna och guld på grafit skorna. Upprätta efter ca 7-8 liter

BODY & CHASSIS

	FRONT	REAR
Wing	–	Composite

Body	EAZY
Chassis	Kit
Chassis brace - rear	None
Chassis sideguards	Med
Front top deck	Composite
Front upper arm wing	None
Rear wing cut-out holes	6
Rear wing holes diameter	9 mm
Rear wing position	Mid
Rear wing wickerbill	No
Weight: total	3406 g

NOTES Bakvinge: 6st hål i bakkant och 6st hål i nedre kant

TIRES

	FRONT	REAR
Tire brand / type	Hotrace Amazonas	Hotrace Amazona
Tire compound	Soft	Soft
Tire condition	New	New
Wheel brand / type	Hotrace	Hotrace

ELECTRONICS

Radio brand	Futaba
Radio EPA brake	50%
Radio EPA throttle	71%
Radio model	10PX
Receiver battery	2s 1800mah
Steering servo brand	SRT
Steering servo model	BH9022
Throttle servo brand	SRT
Throttle servo model	BH9027

NOTES EPA styrning 88%true
Exp styrning -20%