SET-UP SHEET

XB2'26 SET-UP SHEET VER. 1 ©XRAY 2024

XRAY XB2'26

RACE	
TRACK	Speed Factory
NAME	Big Steely
DATE	October 18, 2026

LAPS		BEST LAP TIME	sec
QUALIFYING POSITION		FINAL POSITION	

TRACK

SIZE	OPEN	MEDIUM	TIGHT
TRACTION	VERY-LOW	MEDIUM	VERY-HIGH
SURFACE	SMOOTH	MEDIUM	BUMPY
TYPE	CLAY	CARPET	ASTRO
CONDITION	BLUE GROOVE	HARD PACKED	DRY
	GLUED	DUSTY	LOAMY	WET

TRANSMISSION

BALL DIFF | GEAR DIFF | ACTIVE DIFF

DIFFERENTIAL — OIL 30,000 cSt — 60° 90° 120°

SATELITE GEARS — COMPOSITE | STEEL — GEARS 2 | 4

SLIPPER 0.1 mm — SOLID AXLE

2-PAD SLIPPER CLUTCH PLATES — VENTILATED | STANDARD — KIT — SLIPPER PADS

GEARING

PINION	SPUR GEAR
30 T	72 T

GEAR BOX

TYPE: FRONT LCG 3G | 5G | REAR 3G LCG — HARDNES: KIT | GRAPHITE

SHOCKS

FRONT		REAR
3 dot	SPRINGS	3 dot
500 cst	OIL	300 cst
2 HOLES 3 x 1.5	ø1.6mm / ø1.8mm	2 HOLES 3 x 1.6
HOLES	ø mm / ø mm	HOLES

CAP: KIT ALU | ALU KIT — Previous 0 -1 -1 | -1 -1 0 Previous

Piston: 2.0 | 2.5 KIT Precis. — 2.5 | 2.0 Precis. KIT

Downstop shim (INSERT UNDER PISTON): 0 mm | mm 0

Length: 21 mm | mm 25

Upstop shim (INSERT ABOVE COLLAR): 0 mm | mm 0

COMP. / ALU: 0mm, -2mm, -4mm, -6mm — COLLAR

BALL JOINT: +4mm +2mm 0mm | 0mm +2mm +4mm

ANTI ROLL BAR

FRONT	THICKNESS	REAR
1.2 /mm		1.4 /mm

TIRES

FRONT		REAR
JC concepts Foss bite	BRAND	JC concepts Foss bite
Pink	COMPOUND	Pink
None	INSERTS	Yes
Kit	WHEELS	Kit

ELECTRONICS

MOTOR	Hobbywing	Hobbywing	SPEEDO
SERVO	ProTek	Gens Ace	BATTERY

BODY	TOTAL WEIGHT
Epsilon 2C Light LIGHT	1500 /g

COMMENT

Setup: My Base Setup

FRONT — Open in So Dialed App — APPLIED ◉ ☒ APPLIED — REAR

More: sodialed.com/setups

CASTER BLOCK: MEDIUM | HARD | GRAPHITE | ALU — STEER. ANGLE SCREW

LONGER BUSHINGS: UP | DOWN

ALU C-HUB: UP /mm | DOWN /mm

STEERING BLOCK: MEDIUM | HARD | GRPHITE | ALU

CAMBER LINK LOCATION — SHIM 1 /mm — LOWER SHOCK POSITION

UPPER SHOCK POSITION: 6 DOT | 4 DOT — SHIM 0 /mm — MEDIUM | HARD | GRAPHITE | ALU

DRIVE SHAFT: KIT — SHIM 2 /mm — SHIM 3 /mm — REAR UPRIGHT: HIGH | LOW

LOWER SHOCK POSITION — #325341 ADJ. DRIVE AXLE

ARM MOUNT: 0° KIT | 0° ALU | -3° ALU | +3° ALU | 0° BRASS — TOTAL 24.5 KICK-UP°

FRONT WING: YES | NO — KIT | OTHER — Wide, ribbed

STEERING BUMP STEER: SHIM 1 /mm — ACKERMANN SHIM 1 /mm — CASTER BUSHINGS 0° 2.5° 5°

KICK-UP° — ARM MOUNT 0° + CASTER BUSHING 0° = TOTAL 22° KICK-UP

Cutting line +/- from the base line: 0 +/- mm — Wing length: full /mm — SHOCK TOWER: 2 /mm

Offset wing mounting behind the rear shock tower.

WING TYPE: Lush — **CENTER FIN**: YES | NO — **WING POSITION**: UP | DOWN

FRONT TOE: 0 ° — OUT

OFFSET: +1.5 mm

WHEELBASE: 0 /mm

ROLL CENTER: KIT | ALU

STEERING: PLATE: KIT | ALU — ARMS: KIT | ALU

EXTENSION: 1 DOT | 2 DOTS | 3 DOTS

SERVO BRACE: YES | NO — SERVO POSITION 1 2

REAR TOE: 2 ° — IN

OFFSET: +3.75 mm

BATTERY PLACEMENT: LONG SIDE FRONT | LONG SIDE REAR

MOTOR PLATE: 1 DOT-KIT

WHEELBASE: 3 /mm

BATTERY SIZE: STD. SHORT | LOW SHORT

ROLL CENTER: ALU - KIT | GRAPHITE | COMP.

SIDE BRACES: KIT | GRAPHITE

COOLING: FRONT | REAR

REAR

REAR ROLL CENTER SUSPENSION HOLDERS

RR 0.5° 1° XRAY 3° — SHIM 0 /mm SHIM

RF 0.5° 1°

RR 0.5° 1° XRAY 1° — SHIM /mm SHIM

FRONT CAMBER: -2 /°

GLUING SIDEWALL: YES | NO

FRONT ARM: MEDIUM | HARD | GRAPHITE

ARM TYPE: SHORT - KIT | LONG

DIFF HEIGHT: -2 /°

REAR CAMBER

CUTTING PINS: IN | OUT — NO | NO

REAR ARM: MEDIUM | HARD | GRAPHITE

ARM TYPE: STANDARD | DISENGAGED

RIDE HEIGHT 13 /mm — RIDE HEIGHT #107763 GAUGE — 13 /mm RIDE HEIGHT

LOWER ECCENTRIC SHOCK BALL

FRONT | REAR — FRONT | REAR

ARM MOUNT BALANCE #293085 HUDY Pure Tungsten Weight - 10g.

BALANCE /g — BALANCE /g — BALANCE /g

CHASSIS BRACE: 3G | 5G

SERVO WEIGHT: STANDARD | LOW PROFILE

FRONT CHASSIS FLEX

ELECTRONICS PLATE: NO | GRAPHITE | WEIGHT

REAR CHASSIS FLEX

CHASSIS: KIT | 2.5mm | 2.0mm — MID-SIZE | SHORT | EXTRA SHORT

ARM SHIM 0 /mm

reset all