DRIVER:	Daniel Morris	**TRACK:**	Brendale	**TRANSMITTER:**	Futaba	**THROTTLE SERVO:**	Futaba	**TIRES:**	Matrix Xtreme
DATE:	October 3, 2026	**SURFACE:**	ROUGH ○ SMOOTH ○ Medium	**RECEIVER:**	Futaba	**THROTTLE EXPO:**		**TIRE SIZE (F/R):**	67 74
OUTSIDE TEMPERATURE°C:	25C/77F	**LAYOUT:**	TECHNICAL ○ MIXED ○ FAST●	**STEERING SERVO:**	Futaba	**THROTTLE SPEED:**		**ADDITIVE:**	
TRACK TEMPERATURE°C:		**TRACTION:**	LOW ○ MEDIUM ● HIGH ○	**STEERING EXPO:**		**1st GEAR PINION/SPUR:**	6119	**ADDITIVE TIME (min):**	
VER. 0705-1		**RACE:**	Qlds 26 **RESULT:** 1	**STEERING SPEED:**		**2nd GEAR PINION/SPUR:**	24 57		

SHOCK (mm) UP ● LOW ○ — 3

OFFSET — 1mm

OPT T2159

WHEELBASE(0~-2mm) — -2

CAMBER° — -2

TOE OUT° — -1

STEERING° (outside) — 21

DOWNSTOP(mm) — .5

RIDE HEIGHT (mm) — 19

TRACK WIDTH (mm) — 250

BUMPER WEIGHT

LONG ↔ SHORT

POSITION F ● R ○

ST (mm)

TH (mm)

(mm)

HEIGHT (mm)

(mm)

CAMBER° — -3

TOE IN° — 2.5

DOWNSTOP(mm) — 8

RIDE HEIGHT (mm) — 10

TRACK WIDTH (mm) — 260

SHOCK POSITION — 1

OFFSET (mm) — 3

SHOCK POSITION

H2159-B ○ **UP** ●
H2168 ○ **LOW** ○

Short — Med

H0555C/D/E - H2509 - H2510

SHIM (mm)		**SHIM (mm)**
0		0
1 x 1.3mm	**PISTON**	**PISTON** 2-hole
1.8mm Yellow	**SPRING**	**SPRING** New option
700 cst	**OIL#**	**OIL#** 700 cst
12.5	**(mm)**	**(mm)** 13.5

2.2 2.3 ● 2.4 | **2.8 2.9 ● 3.0**

CASTER (mm) — 1

ROD SHIM (mm) — 2

SCREW USED ○ **NOT USED** ○

INSERT DOT POSITION

FRONT ● **REAR** ○

UP ● **LOW** ○

UP ○ **LOW** ●

INSERT DOT POSITION

FRONT ○ **REAR** ○

A - ARM ○

I - ARM ●

H2164 YES ○ **NO** ○

CAR OVERALL WEIGHT (g) 2321

ADDED WEIGHTS IN GRAMM:

BATTERY (g)

H2412 (18g) □

WEIGHT BALANCE F / R ○○○○○○○

INFO Setup: Brendale qlds 26

Open in So Dialed App

More: sodialed.com/setups

STANDARD ○
HARD (OPT) ●

□ **CUTTED**

15gr mid, 10gr under rear radio & 18gr under mid shaft

BODYSHELL & WING TYPE — Xtreme Hyper Pre Cut

DISTANCE TO BUMPER — **(mm)** 5mm

BODYSHELL WEIGHT (g)

FRONT ← → **REAR**