

Reflex Racing RX28D/SE Gen 3

Setup: 2500 pan · [DJ](#) · Oct 25, 2026

so dialed

Open/save in RC Setup App →



Scan to open in the app

TRACK	
Type	Indoor rcp foam
Grip / moisture	Medium

FRONT SUSPENSION

Ackermann: servo position	Front
Anti-roll bar	Hard
Camber	-0.5 degrees
Caster	2 degrees
Downstop	? mm
Droop	0.5 mm
Knuckle shims - bottom	1 mm
Knuckle shims - top	0 mm
Ride height	1.75 mm
Shocks: tower shims	0 mm
Toe	-0.5 degrees
Toe: link length	? mm
Track width	74.77 mm

BODY & CHASSIS

Battery position	Rear
Body	PN pan
Body mounting	Posts
Bumper	Carbon fiber LMP
Chassis	SE

REAR SUSPENSION

Center pivot chassis shims	0 mm
Droop	0 mm
Ride height	1.75 mm
Ride height: axle carrier shims	0 mm
Side link shims - F	0 mm
Track width	76.34 mm
Track: wheel shims	0 mm

DRIVETRAIN

Axle	Aluminum
Differential balls	Carbide
Differential lube	Amsoil
Differential type	Gear
Pinion	16 teeth
Spur	51 teeth

ELECTRONICS

Battery brand	PN
Battery C rating	60 C
Battery capacity	360 mAh
Battery model	2S
ESC brand	Hobbywing
ESC model	Mini 28
Motor brand	PN
Motor Kv constant	2500 Kv
Motor model	V5
Servo brand	Reflex Racing

SHOCKS

Center shock fluid	40,000 cst
Center shock spring	Hard gold

CENTER SHOCK

Front mount	Front
Front shims	0 mm
Rear mount	Front
Rear shims	0 mm
Fluid brand	Marka
Front damper fluid	40,000 cst
Front springs	Hard linear gold
Side damper fluid	40,000 cst
Side damper shims - in/out	0 / 0 mm
Side spring pre-load	0 mm
Side springs	Hard silver

TIRES

	FRONT	REAR
Tire adhesive	Tape	Tape
Tire brand / type	PN KS low profile medium	Marka V1RR10
Tire diameter	Width 11mm	Width 14mm
Wheel brand / type	Reflex Racing / machine nylon	Reflex Racing / machined nylon
Wheel offset	-1.5 mm	0 mm