More: sodialed.com/setups
Open in So Dialed App

SET-UP SHEET

X4'26 SET-UP SHEET VER.1 ©XRAY

XRAY X4'26

RACE	Hudy Series
TRACK	Huge RC
NAME	Lawrence Macalinao
DATE	August 22, 2026

QUAL POSITION	FINAL POSITION	BEST LAPTIME	LAPS	TIME
		/sec	/	

TRACK

TRACK SURFACE		CARPET	ASPHALT
TRACK LAYOUT	TECHNICAL	MIXED	FAST
TRACTION	LOW	MEDIUM	HIGH

TRANSMISSION

FRONT			REAR	
GEAR DIFF OIL	/cSt	FRONT SOLID AXLE	GEAR DIFF OIL	8,000 /cSt

UP / DOWN — SOLID & DIFF POSITION — UP / DOWN

PINION	SPUR GEAR	F. DRIVE RATIO
50 /T	90 /T	

SHOCKS

FRONT		REAR
2.5-2.8C	XRAY SPRINGS	2.6C
350 cst	OIL /Cst	350 cst
25	REBOUND %	25

4 HOLES / PSS — 1.1mm / 1.2mm

SHOCK LENGTH: 7.5 /mm (front) — 7.5 /mm (rear)

ANTI-ROLL BAR

1.3 THICKNESS/mm — 1.2 THICKNESS/mm

TIRES	40	40
ADDITIVE	Mighty Gripper Yellow	Mighty Gripper Yellow
ADDITIVE TIMING		
WIPE OFF TIME		
TIRE WARMERS	Timing: / Temp.:	Timing: / Temp.:

SIDE WALL GLUE — DIA. /mm

FRONT TIRES — ADDITIVE AREA /mm

TOTAL WEIGHT	/g	WEIGHT BALANCE	FRONT 50 / 50 %

MOTOR	Muchmore	TIMING	
ESC	Elceram	BATTERIES	Gens Ace
BODY	Venturi	WING	

BODY POSITION

/mm — Dimension from body post to window bottom line

Dimension from body post to upper holder

WING SIDE PLATE YES / NO

Dimension from edge to surface /mm

WAVE BRACE

TOP DECK / BULKHEADS / NONE

GF 1.6 2.0 SCREWS 2.0 1.6 GF

SHIMS

Rear used in front

2.0 1.6

#301092 NONE BEARING

CUTTING

Setup: X4 Huge

COMMENTS

FRONT & REAR SUSPENSION

FRONT CASTER 5° 4° 3° — Adjust with eccentric bushings

Upper links CASTER

BUMP STEER 4 /mm — HEIGHT 19 /mm — SHIM 4 /mm

SHIM 3 /mm

0.5° 1.5° 2.5° 3.5° 4.5° 5.5° — Adjust with eccentric bushings

Upper links CASTER

2 /mm FF — RIDE HEIGHT /mm — FR 2 /mm — SERVO SAVER / SERVO HORN

TOE GAIN 2 /mm — 2 /mm RF — RIDE HEIGHT — RR 2 /mm

FRONT

-2 /degr. CAMBER — Left=Right

BODY STOP YES / NO /mm

SHIM /mm 2

FF 2 / FR 2 SHIMS /mm 2

FRONT HUB MEDIUM / HARD — GRAPH. / ALU

#107730 Droop Gauge

#107712

DOWNSTOP /mm — Set with shocks / Set without shocks

YES NO YES NO SUSPENSION FLEX

DRIVE SHAFT 58mm 59mm

SHIM /mm 0.5 — 22 UPSTOP /mm — DROOP /mm

Set with shocks / Set without shocks

REAR

-2 /degr. CAMBER — Left=Right

BODY POST VERTICAL / HORIZONT.

SHIM /mm 2

RF 0.5 / RR 0.5 SHIMS /mm 2

REAR HUB MEDIUM / HARD — GRAPH. / ALU

#107712

DOWNSTOP /mm — Set with shocks / Set without shocks

YES NO YES NO SUSPENSION FLEX

DRIVE SHAFT 52mm 54mm

SHIM /mm 0.5 — 22 UPSTOP /mm — DROOP /mm

Set with shocks / Set without shocks

FRONT TOP VIEW REAR

TOE OUT Left=Right — ACKERMANN 1 /mm — SHORT LiPo BRASS WEIGHT YES / NO YES / NO — TOE IN Left=Right

UPPER CLAMP KIT / -1mm — UPPER CLAMP FLEX — 40g — BRASS WEIGHT FOR MOTOR MOUNT — 40g — UPPER CLAMP FLEX — UPPER CLAMP KIT / -1mm

SHIMS 0 /mm

FRONT UPPER CFF™ ARM - S / LINKS SHORT / LINKS LONG

STEERING BRIDGE YES / NO — STEERING SHIM SIZE — PLATE 8.0mm KIT / 7.5mm

REAR UPPER CFF™ ARM - S / LINKS SHORT / LINKS LONG

HUB OFFSET — SHIM /mm 0 — HUB OFFSET — SHIM /mm 0

FRONT BOTTOM VIEW REAR

BUMPER 3D - KIT / FOAM

STEER. LOCK 23 /degr.

T-BRACE ALU / BRASS

SERVO HOLDER — MOTOR MOUNT — CHASSIS T-BRACE

CHASSIS GRAPHITE / ALU / ALU 1.5mm

FRONT ARMS MEDIUM / HARD / SHORT

REAR ARMS MEDIUM / HARD / SHORT

reset all