Willspeed Fast Fox B7 Conversion

Setup: Lost Place Racers · Marco Steinbuechel · Aug 23, 2026

so dialed
Open/save in RC Setup App →

Scan to open in the app

EVENT	
Event	Training

TRACK	
Track	Lost Place Racers
Type	Indoor astroturf
Grip / moisture	High / Dry
Surface / layout	Medium / Open
Air temp	20°C (68°F)
Track temp	20°C (68°F)

RESULTS	
Best lap	31.1 s

FRONT SUSPENSION

ACKERMANN	
Inner steering link shims	1 mm
Steering plate	+1mm
Anti-roll bar	1.2 mm
Arms	Carbon
Axle height: steering block shims	+0 mm
Bellcrank link length	2 mm
Bulkhead	+/-2.5 deg aluminum
Bulkhead shims	0 mm
BUMP STEER	
Bellcrank orientation	Up
Outer steering link shims	1 mm
Camber	-1 degrees
CAMBER LINKS	
Inner	In
Inner shims	3 mm
Outer mount	-1 mm
Outer shims	2 mm
Caster: caster block inserts	+5 degrees
Kick-up	+2.5 degrees
Ride height	14 mm
Servo horn shims	1 mm
SHOCKS	
Front mounts	Mid
Pushrod arm mounts	Mid
Pushrod rocker mounts	Mid
Rear mounts	Rear
Rocker pivot	Rear
Steering block KPI	2 degrees
Steering blocks	Standard
Steering stop shims	0 mm
Toe	-1.5 degrees
Track: wheel hexes	6.5 mm
Wheelbase: caster block shims	Long

REAR SUSPENSION

Anti-roll bar	0 mm
Arms	Standard
Axle height: hub inserts	+3 mm
C mount	Standard
C mount inserts	1 up and out
Camber	-1 degrees
CAMBER LINKS	
Inner	Out
Inner shims	1 mm
Outer mount shims	0 mm
Outer shims	2 mm
D mount	Standard
D mount inserts	0 center
Differential height	3 mm
Hubs	HRC
Ride height	14 mm
SHOCKS	
Front mounts	4
Pushrod arm mounts	Mid
Pushrod rocker mounts	Mid
Rear mounts	Mid
Rocker pivot	Front
Track: wheel hexes	5 mm
WHEELBASE	
Arm shims	Long
Hub shims	Long

TIRES

	FRONT	REAR
Tire brand / type	Hudy Astro	Hudy Astro
Tire compound	Medium	Medium
Tire insert	None	Hudy
Wheel brand / type	JC	JC

ELECTRONICS

Battery capacity	4800 mAh
Battery model	MC3
ESC brand	Hobbywing
Motor brand	Ruddog
Motor wind	5 turns
Servo model	SRT BHMX2

SHOCKS

	FRONT	REAR
Cup offset	9 mm	5 mm
Eyelet length	+0 mm	+0 mm
Limiters - ext	4 mm	0 mm
Limiters - int	0 mm	0 mm
Oil weight	650 cst	450 cst
Pistons	2mm 2x1.6mm holes	2.5mm 2x1.9mm holes
Springs	WS green	WS Green
Stroke	23.8 mm	28 mm

Shock bodies	Standard
Shock oil brand	Team Associated
Shock shafts	Chrome

DRIVETRAIN

Clutch pads	2 x 19mm
Clutch type	Slipper
Differential fluid	100,000 cst
Differential fluid brand	Team Associated
Differential type	2-Gear
Drive ratio - internal	2.60
Driveshafts	Universal
Pinion	19 teeth
Spur	78 teeth

BODY & CHASSIS

	FRONT	REAR
Wing	B7	JC

Battery position	2
Body	Fast Fox Formula
Chassis	Carbon
FLEX	
Gearbox	B7.1
Side rails	Standard
Top plate	Standard
Rear wing angle	0 degrees
Screws & turnbuckles	Avid Titanium