Custom Works Enforcer 7

Setup: My Base Setup · rmxart · Nov 2, 2026

so dialed
Open/save in RC Setup App →

Scan to open in the app

TRACK	
Track	Auburn Rc
Grip / moisture	Dry
Surface / layout	Smooth / Open
Air temp	120°F (49°C)

FRONT SUSPENSION

Ackermann - L/R	**- / -**
Axle spacers - L/R	**- / -**
Camber - L/R	**R 2.0 negative left 1.0 positive**
CAMBER LINK	
Inner stud location - L/R	**- / -**
Inner stud spacers - L/R	**- / -**
Outer stud location - L/R	**- / -**
Caster - L/R	**35 degrease**
Ride height - L/R	**Front 12 mm rear 12mm**
SHOCKS	
Arm mounting hole - L/R	**- / -**
Tower mounting hole - L/R	**- / -**
STEERING LINK	
Inner stud spacers - L/R	**- / -**
Outer stud spacers - L/R	**- / -**
Toe	**0 degrees**

NOTES Customeorks 5 front shock tower

REAR SUSPENSION

Anti-squat - L/R	**- / -**
Axle spacers - L/R	**- / -**
Camber - L/R	**- / -**
CAMBER LINK	
Inner stud location - L/R	**- / -**
Inner stud spacers - L/R	**- / -**
Outer stud location - L/R	**- / -**
Outer stud spacers - L/R	**- / -**
Ride height - L/R	**- / - mm**
SHOCKS	
Arm mounting hole - L/R	**- / -**
Tower mounting hole - L/R	**- / -**
Toe - L/R	**- / -**
Wheelbase (arm spacers) - L/R	**- / -**
Wheelbase (hub spacers) - L/R	**- / -**

SHOCKS

	FRONT	REAR
Bodies - L/R	**- / -**	**- / -**
Cups - L/R	**- / -**	**- / -**
Oil weight - L/R	**- / -**	**- / -**
Pistons - L/R	**- / -**	**- / -**
Shaft length - L/R	**- / - mm**	**- / - mm**
Shock length - L/R	**- / - mm**	**- / - mm**
Springs - L/R	**- / -**	**- / -**

DRIVETRAIN

Clutch type	**Direct drive**
Differential fluid	**10,000 cst**
Differential type	**Ball**
Drive ratio - final	**2.6**
Spur	**78 teeth**

TIRES

	FRONT	REAR
Tire brand / type - L/R	**- / -**	**- / -**
Tire compound - L/R	**- / -**	**- / -**
Tire insert - L/R	**- / -**	**- / -**
Wheel brand / type	**DE Racing**	**–**