Reflex Racing RX28D/SE Gen 3

Setup: My Base Setup · awl · Oct 6, 2026

so dialed
Open/save in RC Setup App →

Scan to open in the app

TRACK

Track	SRC Letchworth
Type	Indoor rcp foam
Grip / moisture	Medium
Surface / layout	Bumpy / Medium
Air temp	20°C (68°F)

FRONT SUSPENSION

Ackermann: servo position	Front
Anti-roll bar	Med
Camber	-2 degrees
Camber: upper arm length	23.2 mm
Caster	2 degrees
Downstop	1 mm
Knuckle shims - bottom	1 mm
Knuckle shims - top	0 mm
Ride height	2.2 mm
Shocks: tower shims	0 mm
Toe	-2 degrees
Toe: link length	25 mm

TIRES

	FRONT	REAR
Tire adhesive	Tape	Tape
Tire brand / type	Marka HG low profile slick	Marka 10 radial
Wheel brand / type	Reflex	Reflex
Wheel offset	0 mm	3 mm

NOTES 8.5mm wide front wheels

11mm wide rear wheels

REAR SUSPENSION

Center pivot chassis shims	0 mm
Ride height	2.2 mm
Ride height: axle carrier shims	1 mm
Track: wheel shims	0.5 mm

DRIVETRAIN

Axle	Aluminum
Differential balls	Carbide
Differential lube	Reflex
Differential tightness	Medium to tight
Differential type	Ball
Pinion	13 teeth
Spur	53 teeth

ELECTRONICS

Battery brand	GK Body
Battery capacity	400 mAh
ESC brand	Hobbywing
ESC model	Ezrun28
ESC settings	No boost or turbo 6% drag brake at 80% power
Motor brand	Omg
Motor Kv constant	2500 Kv
Motor model	Aurora 2500
Radio brand	Flysky
Radio model	NB4+
Receiver brand	Flysky
Receiver model	GMR
Servo brand	Omg

SHOCKS

Center shock fluid	15,000 cst
Center shock spring	Med silver
CENTER SHOCK	
Front mount	Front
Front shims	0 mm
Rear mount	Front
Rear shims	0 mm
Front damper fluid	15,000 cst
Front springs	Hard linear gold
Side damper fluid	20,000 cst
Side damper shims - in/out	0 / 0 mm
Side springs	Med black

BODY & CHASSIS

Body	Jomereuma GT-01
Bumper	3D printed

ESC SETTINGS

Brake: Drag	6 %