



TRACK	
Type	Outdoor p-tile
Grip / moisture	Low

FRONT SUSPENSION

Ackermann: steering arms	A
Anti-roll bar	1.2 mm
Axle height: spindle shims	Low

BUMP STEER	
Inner steering link shims	0 mm
Outer steering link shims	1 mm
Camber	-1 degrees

CAMBER LINKS	
Inner	Down
Outer shims	0.5 mm
Caster	5 degrees
FF mount inserts	1 up
FF mount shims	0 mm
FR mount inserts	0 center
Ride height	8 mm

SHOCKS	
Arm mounts	In
Tower mounts	Up / mid
Toe	-1 degrees
Track: wheel hexes	5.2 mm
Wheelbase: arm shims	Short

REAR SUSPENSION

Anti-roll bar	1.3 mm
Camber	-1 degrees

CAMBER LINKS	
Inner	Down
Outer	Mid
Outer mount shims	0.5 mm
Outer shims	0 mm
Ride height	10 mm
RR mount inserts	0 center

SHOCKS	
Arm mounts	Out
Tower mounts	Up / mid
Toe	3.5 degrees
Track: wheel hexes	5.2 mm

BODY & CHASSIS

Body	Kit
Bumper	001 Soft
Chassis	Aluminum 2.5mm

TIRES

	FRONT	REAR
Wheel brand / type	PR ST 1	PR ST 1

SHOCKS

	FRONT	REAR
Limiters - int/ext	0 / 0 mm	0 / 4 mm
O-rings	Transparent	Transparent
Oil weight	300 cst	450 cst
Pistons	2X1.9	2 x 1.6mm
Springs	2.97lb Transparent	2.70lb Yellow
Stroke	23.3 mm	23.3 mm
Bodies	12.8 mm	
Shock oil brand		

DRIVETRAIN

DIFFS	
Center fluid	20,000 cst
Center type	2-gear
Front fluid	5,000 cst
Front type	2-gear
Rear fluid	3,000 cst
Rear type	2-gear
Drive ratio - internal	2.6
Drive type	Differential
Driveshafts - F	CVD
Driveshafts - R	CVD
Spur	80 teeth