1RC Super Modified 1/18

Setup: 2026-10-04 S&J Raceway · George Mari · Oct 9, 2026

so dialed
Open/save in RC Setup App →

Scan to open in the app

EVENT

Event	2026-10-04 Weekly club race
Class	Super Modified

TRACK

Track	S&J RC Raceway
Type	Indoor carpet
Grip / moisture	High / Dry
Surface / layout	Smooth / Medium

RESULTS

Race type	Main
Race number	A
Finish	3rd
Best lap	2.70 s
Average lap	3.131 s
Laps / time	94 / 4:56.420

FRONT SUSPENSION

Kingpins	**Solid**
LF caster	**+2**
RF caster	**+2**
Servo arm hole	**Lower**
Servo arm type	**Servo saver**

TIRES

LF tire compound	**Standard**
LR tire compound	**Standard**
RF tire compound	**Standard**
RR tire compound	**Standard**

NOTES Glue on outside 1/8 inch of RF tire.

ESC SETTINGS

BRAKE

Drag force	**5 %**
Initial force	**0 %**
Max force	**50 %**
Low voltage cut-off	**Disabled**
Max reverse force	**50 %**
Neutral range	**9 %**
Overheat warning	**Enabled**
Running mode	**FWD / Brake**
Start mode / punch level	**4**
Timing	**0 degrees**

REAR SUSPENSION

LR hex offset	**0 mm**
RR hex offset	**0 mm**

BODY & CHASSIS

Motor heatsink	**Yes**
Top wing mount hole	**Standard wing mount not adjustable**

ELECTRONICS

Battery brand/model	**Turnigy**
Battery capacity	**300 mAh**
Battery cells	**2**
Battery type	**LiPo**
ESC	**1RC**
Motor brand/model	**1RC**
Motor Kv constant	**10,000 Kv**
Radio	**Flysky GT-5**
Radio dual-rate	**65 %**
Radio EPA brake	**100 %**
Radio EPA throttle	**100 %**
Receiver	**Flysky GT2E**
Servo	**1RC**
Transponder ID	**0824**

NOTES Steering Left EPA - 55
Steering Right EPA - 60

SHOCKS

LF body	**Plastic**
LF grease	**AE Green Slime**
LF o-ring	**Clear**
LF pre-load	**0 mm**
LF spring	**Medium**
LF stroke	**7.0 mm**
LR body	**Plastic**
LR grease	**AE Green Slime**
LR o-ring	**Clear**
LR pre-load	**0 mm**
LR spring	**Medium**
LR stroke	**7.0 mm**
RF body	**Plastic**
RF grease	**AE Green Slime**
RF o-ring	**Clear**
RF pre-load	**0 mm**
RF spring	**Medium**
RF stroke	**7.0 mm**
RR body	**Plastic**
RR grease	**AE Green Slime**
RR o-ring	**Clear**
RR pre-load	**0 mm**
RR spring	**Medium**
RR stroke	**7.0 mm**
Shock caps	**Drilled**